

TOWNSHIP 25 RANGE 02 POINT IDENTIFIER # 620320

PRIMARY CORNER DESCRIPTION SW 1/16 Sec 24

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

V.W. Hosford - Oct. 13, 1955 - C.S. File 42/20 & M16-5  
-----  
The exact point for this corner falls within a 28" cedar tree, which I mark SW1/16 S24 PS 253, from which  
    A hemlock 20" in dia., bears N.76°E., 22.4 ft., mkd: SW 1/16 S24 253 BT.  
    A hemlock 12" in dia., bears S.53°W., 35.5 ft., mkd: SW 1/16 S24 253 BT.

Weyerhaeuser Co. Glen McChesney - 5/20/1958 - C.S. File 53/112-36  
-----  
Found - Hosford's 28" Cedar corner tree, (fd scribed on four sides) and both BTs (fd scribed)  
          Hosford's 20" Hem, bears N.76°E., 22.1 ft, added "W" nail and plate.  
New - 40" Fir, bears S.24°E., 22.0 ft. "W" nail and plate.

Douglas Co. Surveyors Office - Crew: Stephen Flauser & Jeff Lorsung - 6/20/2024 - C.S. File 67/58-16  
-----  
Found - Burned sawn 22"x2½' solid cedar stump, no marks visible, 2½" BC in center (no record, see note)  
          BC mkd: SW 1/16  
                  S24  
                  LS 2339  
                  2017  
          Burned, rotted 30"x2½ ft. hemlock stump, N. 76°E., 23.2 ft. scribe S24 visible.  
          Burned, sawn 31"x2 ft. hemlock stump, S.53°W., 36.4 ft., orig. face visible inside.  
          Burned, rotted 34"x 3 ft. Fir stump, S.20°E., 22.4 ft. (rec. S.24°E., 22.0 ft) to nail in face, add 3½" mag nail to face.  
New - Burned, sawn 27"x1½ ft. hemlock stump, S.72°W., 12.3 ft., 3½" mag nail top center.  
Note - Compass decl. 14¼°E.  
          Note written by Jeff Lorsung: "I Spoke with David Edwards, He said they did not use the corner for their map, but his guys were there and found the OBT's. They had no record of setting the cap. We agreed to just write it up as a previously unrecorded accessory".  
Oregon Coordinate Reference System  
Cottage Grove - Canyonville Zone  
N 198421.038                   E 282217.140