

TOWNSHIP 25 RANGE 02 POINT IDENTIFIER # 620360

PRIMARY CORNER DESCRIPTION NW 1/16 sec 24

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

V.W. Hosford - Oct. 13, 1955 - C.S. File 42/20 & M16-5

Set a 4" hemlock post marked NW 1/16 S24, from which
A hemlock 16" in dia., bears S.37°E., 32.6 ft., mkd: NW
1/16 S24 PS 253 BT
A hemlock 16" in dia., bears S.29½°W., 22.3 ft., mkd: NW
1/16 S24 PS 253 BT

David Edwards - For: Roseburg Resources Co - 3/2020 - M176-59

Set - 5/8"x30" STEEL REBAR WITH 2½" dia. aluminum cap mkd.
as per the 2009 BLM. manual, "ROSEBURG RESOURCES
CO" and "LS 2339" and "2020"
A 48" dia, 15 ft tall fir snag (C.S. 58/8-40) bears
S.83½°E, 7.2' (S.84°E., 7.0').
A 24" dia. hemlock with healed blaze (M 16-5) bears
S.36½°E., 32.2' (S.37°E., 32.6').
A 20" dia, 6 ft tall stump with vis. scribe (M 16-5)
bears S.28½°W., 22.2' (S.29½°W., 22.3')
New - A 10" dia. hemlock scribed "NW 1/16 S24 BT" bears
S.30°W., 3.2:
A six ft steel post is set 2' south.

Douglas Co. Surveyors Office - Crew: Stephen Flauser & Jeff
Lorsung- 6/17/2024 - C.S. File 67/58-14

Found - 2½" alum. cap ROSEBURG RESOURCES (properly mkd)
proj. 6"
Burnt 37"x15 ft Fir snag S.83½°E., 7.5 ft. (rec. 7.2
ft.) to "W" nail 9.0 ft. to 3½" mag nail right
side center added.
Burnt-sawn 34"x2½ ft. hemlock stump S.36½°E., 33.8
ft (rec. 32.6 ft) add 3½" mag nail top center.
Very burnt 16"x6' fir stub S.28½°W., 22.2 ft. add
3½" mag nail right side center.
6 ft. steel fence post 2.0 ft. South.
Note - Mon on northerly flat ground ≈ 140 ft South of dirt
access road.
Compass decl. 14¼°E.
Oregon Coordinate Reference System
Cottage Grove - Canyonville Zone
N 201050.606 E 282212.508