

TOWNSHIP 25 RANGE 02 POINT IDENTIFIER # 620400

PRIMARY CORNER DESCRIPTION W 1/16 Secs. 13 & 24

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

V.W. Hosford - Dec. 30, 1953 - C.S. File 41/245

Set a 3" fir post for corner from which
A fir 10" in dia., bears N.30°E., 20.8 ft., mkd: 1/16S 13
- PS 253 BT
A fir 10" in dia., bears S.6½°E., 7.7 ft., mkd: 1/16S 24
- PS 253 BT

BLM resurvey by A. Bert Skeesick, Cadastral Surveyor Group
#1979, surveyed 2001/2002- (DCS0 rec. Vol. 54 Pages 20913)

The W 1/16 sec. cor. of secs. 13 and 24, established by V.W.
Hosford, in 1953, and is accepted as the cor., determined at
Hosford record bearing and distance from his bearing trees
A fir, 19" dia., bears N.30°E., 20.8 ft., with healed
blaze.

A fir, 20" dia., bears S.6°E., 7.7 ft., with healed blaze.
At the corner point

Set an iron post, 28" long, 2½" dia., 16" in the ground, in
a mound of stone, 3 ft. base, to top, with brass cap mkd.

T 25 S R 2 W

W 1/16 $\frac{S 13}{S 24}$
2002

Deposit a magnet in a white plastic case at the base of the
iron post.

Douglas Co. Surveyors Office - Crew: Stephen Flause & Jeff
Lorsung- 6/20/2024 - C.S. File 67/58-15

Found - 3¼" brass cap (properly mkd) in rough stone mound up
10".

Burned-dead 24" D.Fir N.30°E., 21.0 ft. (rec. 20.8
ft) add 3½" mag nail right side center.

Burned out shattered 16"x6 ft D.Fir stump S.6°E.,
7.7 ft., bark scar only center gone.

New - 10"x20 ft. burned Fir snag N.63°E., 12.5 ft. 3½" mag
nail right side center.

Note - Mon on steep west slope old second growth NE quad,
rest clear cut.

Mon is 175 ft ± north of gravel road.

Area burnt 9/2020

Compass decl. 14¼°E.

Oregon Coordinate Reference System

Cottage Grove - Canyonville Zone

N 202378.992 E 282217.077