

TOWNSHIP 25 RANGE 02 POINT IDENTIFIER # 640200

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 25 & 36

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO Survey by Hezikiah H. Johnson, under Contract #721, dated May 1, 1900 (DCSO records Vol. 9 Page(s) 3593)

Set basalt stone 16x12x7", 11" in the ground for ¼ sec. cor. N face, from which

A fir, 14" dia., bears N.65°W., 33 lks., mkd: ¼ S25 BT.

A fir, 14" dia., bears S.61°W., 33 lks., mkd: ¼ S36 BT.

Glen McChesney, Weyerhaeuser Co. - 6/2/1959 - C.S. File 53/112-47

Found - Orig. stone in place.

22" Fir, N.65°W., 21.8 ft., scribing visible on upper face.

24" Fir, S.61°W., 21.8 ft., scars visible.

New - 40" Fir S.86°E., 6.0 ft. with "W" nail & plate.

38" Fir N.81°W., 16.8 ft. with "W" nail & plate.

BLM dependent resurvey by Floyd A. Brooks, Cadastral Surveyor, under Group #350, surveyed April 1962 - (DCSO records Vol. 32 Page(s) 13215)

The ¼ sec. cor. of secs. 25 & 36, monumented with a basalt stone, 16x12x7" firmly set 11" in the ground, marked ¼ on the N face, from which the orig. BTs:

A fir, 26" dia., bears N.65°W., 33 lks. with healed blaze.

A fir, 29" dia., bears S.59°W., 33 lks. with healed blaze.

(Rec. bearing S.61°W.)

At the corner point

Set an iron post, 28" long, 2½" dia., 26" in the ground, with brass cap marked:

¼ $\frac{S\ 25}{S\ 36}$

T25S R2W

1962

Deposit the orig. corner stone alongside the iron post.