

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 13 & 24

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

GLO Survey by Hezikiah H. Johnson, under Contract #721, dated May 1, 1900 (DCSO records Vol. 9 Page(s) 3598)

Set basalt stone 16x12x4", 11" in the ground for ¼ sec. cor. marked ¼ on N faces, from which

A fir, 40" dia., bears N.25°W., 10 lks., mkd: ¼ S13 BT.

A fir, 36" dia., bears S.58°E., 22 lks., mkd: ¼ S24 BT.

BLM dependent resurvey by Floyd A. Brooks, Cadastral Surveyor, under Group #350, surveyed April 1962 -(DCSO records Vol. 32 Page(s) 13218)

The sec. cor. of secs. 13 & 24, monumented with a basalt stone, 16x12x10", firmly set 11", in the ground, mkd. ¼ on the N face, from which the original bearing trees:

A fir, 50" dia., bears N.25°W., 12 lks., with fragmentary scribe marks visible on partly opened blaze. (Record dist., 10 lks.)

A fir snag, 42" diam., bears S.58°E., 24 lks., with healed blaze. (Record dist., 22 lks.)

At the corner point

Set an iron post, 28" long, 21" dia., 24" in the ground, & in a mound of stone, 3 ft. base, to top, with brass cap mkd:

¼ $\frac{S\ 13}{S\ 24}$

T25S R2W

1962

from which new bearing trees

A cedar, 9" dia., bears N.41°W., 18½ lks., mkd S13 BT.

A fir, 10" dia., bears S.48½°W., 33 lks., mkd S24 BT.

Deposit the original corner stone alongside the iron post.

BLM resurvey by A. Bert Skeesick, Cadastral Surveyor under Group #1979, surveyed 2001/2002- (DCSO rec. Vol. 54 Page(s) 20912-3)

The ¼ sec. cor. of secs. 13 & 24, monumented with an iron post, 2½" dia., firmly set, projecting 6" above ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.

¼ $\frac{S\ 13}{S\ 24}$

T25S R2W

1962

from which the remains of the original bearing trees

A sawed, decayed fir stump, 30" dia., bears S.67¼°E., 15.8 ft., with healed blaze. (Record, S. 58° E.)

continued next page

TOWNSHIP 25 RANGE 02 POINT IDENTIFIER # 640400

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 13 & 24

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A fir, 55" dia., bears N.13°W., 7.9 ft., with healed blaze. (Record, N.25°W.)
and remains of bearing trees mkd. by Brooks
A sawed fir stump, 12" dia., bears S.49¼°W., 20.8 ft., with a healed blaze. (Record, S.48½°W., 21.8 ft.)
A cedar, 16" dia., bears N.38½°W., 12.9 ft., with a healed blaze. (Record, N.41°W., 12.2 ft.)
and new bearing tree
A fir, 13" dia., bears S.78¼°W., 37.7 ft., mkd. ¼ S24 BT.
Each new bearing tree has a 2½"x ¼" magnetic nail (Mag Nail) driven at the base right side-center.