

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 1 & 12

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO Survey by Hezekiah H. Johnson, under Contract #721, dated May 1, 1900 (DCSO records Vol. 9 Page(s) 3602)

Set basalt stone 14x10x6", 10" in the ground for ¼ sec. cor. marked ¼ on N faces, from which

An Arbutus, 9" dia., bears S.15°W., 18 lks., mkd: ¼ S12 BT

A fir, 60" dia., bears N.69°W., 61 lks., mkd: ¼ S1 BT.

BLM dependent resurvey Levi E Tallett, Cadastral Engineer (1951) and C. Albert White, Cadastral Surveyor (1963), under Group # 294, surveyed May 1951 - Aug 1963 - (DCSO records Vol. 32 Page(s) 13341)

The Sec. cor. of secs. 1 & 12, monumented w/a basalt stone, 14x10x6", firmly set, marked on N face, from which the OBTs:

A fir, 64" dia., bears N.71°W., 63 lks., blaze healed. (Record: bears N.69°W., 61 lks.)

A madrone, 14" dia., bears S.16°W., 20 lks., partial scribe marks visible. (Record: bears S.15°W., 18 lks.)

At the corner point

Set an iron post, 36" long, 1" dia., 28" in the ground, with brass cap mkd.

¼ $\frac{S \ 1}{S \ 12}$

1951

from which

A fir, 36" dia., bears S.54°W., 134 lks., mkd. ¼ S12 BT.

Bury the original corner stone alongside the iron post.

Fd. Ok by S. Ness 10/1995 - M123-3A&B

BLM Dependent Resurvey by Kenneth W. Saveland, Cadastral Surveyor, under Group No. 2348, Surveyed March/June 2011 - (DCSO records BLM Plat T25-2W 2012-1 & Vol. 58 Pages 22940-1)

The ¼ sec. cor. of secs. 1 and 12, monumented with on iron post, 1" dia., firmly set, projecting 11" above ground. with brass cap (properly) mkd.

from which the remains of the original BTs

A madrone snag, 14" dia., bears S.16¼°W., 13.2 ft., with no marks visible on an open decayed blaze.

A fir, 62" dia., bears N.71½°W., 41.6 ft., with a healed blaze.

and a bearing tree mkd. by Tallett and White

A fir, 45" dia., bears S.54½°W., 88.4 ft., with a healed blaze.

Latitude 43°24'59.35"N. Longitude 122°53'02.91"W.

(NAD 1983 (CORS 96))