TOWNSHIP 25 RANGE 02 POINT IDENTIFIER # 660400

PRIMARY CORNER DESCRIPTION E 1/16 Secs 13 & 24

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

BLM resurvey by A. Bert Skeesick, Cadastral Surveyor under Group #1979, surveyed 2001/2002- (DCS0 rec Vol 54 Pg 20912)

Point for the E 1/16 sec. cor. of secs. 13 and 24.
Set a stainless steel post, 28" long, 2½" dia., 24" in the ground, with brass cap mkd.

T25S R2W

E 1/16 $\frac{\text{S 13}}{\text{S 24}}$

2002

from which
A fir, 10" dia., bears N.16°E., 8.4 ft. mkd. E 1/16 S13 BT
A fir, 17" dia. bears S.20½°E., 21.5 ft. mkd E 1/16 S24 BT
Deposit a magnet in a white plastic case at the base of the stainless steel post.

Ron Rice - For: Seneca Jones Timber Co. 8/2003 - M142-79

Found - 3" BLM BC dated 2002 with the following accessories;
10" D.Fir bears N.16°E., 8.4' (open face scribing visible)
17" D.Fir bears S.20½°E., 21.5' (open face scribing visible)

Douglas Co. Surveyors Office - Crew: Jeff Lorsung- 6/26/2024 - C.S. File 67/58-18

Found - 3" BLM brass cap (properly mkd) on iron pipe.
Burned 12" D.Fir N.18°E., 8.4 ft., healed single blaze, add 3½" mag nail right side center.
Burned 24" D.Fir S.20½°E., 21.5 ft., healed single blaze, add 3½" mag nail right side center.
Steel post along south side.
Alum. post along north side.
New - 18"x2½ ft. hemlock stump S.72°W., 12.0 ft., 3½" mag nail top center.
Note - Mon is ≈ 250 ft. west of gravel road on flat bench, burned timber to NW, other quads burned reprod.
Area burnt 9/2020
Compass decl. 14¼°E.
Oregon Coordinate Reference System
Cottage Grove - Canyonville Zone
N 202304.783 E 284859.165