TOWNSHIP 25 RANGE 02 POINT IDENTIFIER # 660420

PRIMARY CORNER DESCRIPTION SE 1/16 Sec. 13

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

BLM resurvey by A. Bert Skeesick, Cadastral Surveyor under Group #1979, surveyed 2001/2002- (DCS0 rec Vol 54 Pg 20942-3)

Point for the SE 1/16 sec. cor. of sec. 13, at its calculated position.
Set an iron post, 28" long, 2½" dia., 24" in the ground, with brass cap mkd. T25S R2W
SE 1/16
S 13
2002
from which
A hemlock, 9" dia., bears S.35½°E., 21.2 ft., mkd. SE 1/16 S13 BT.
A fir, 11" dia., bears S.66°W., 12.6 ft., mkd. SE 1/16 S13 BT.
Deposit a magnet in a white plastic case at the base of the iron post.

Ron Rice - For: Seneca Jones Timber Co. 8/2003 - M142-79

Found - 3" BLM BC dated 2002 with the following accessories;
9" Hemlock bears S.35½°E., 21.2' (open face scribing visible)
11" D.Fir bears S.66°W., 12.6' (open face scribing visible)

Douglas Co. Surveyors Office - Crew: Jeff Lorsung- 6/25/2024 - C.S. File 67/58-17

Found - 3¼" BLM brass cap (properly mkd) up 4".
Burnt 10" Hemlock Bears S.35½°E., 21.2 ft., healed blaze, add 3½" mag nail right side center.
Burnt 14" D.Fir S.66°W., 12.6 ft., healed blaze, add 3½" mag nail right side center.
Alum. galvanized post 30 Ft. South
Note - Mon is 200'± south of gravel road near bottom of 25' ravine.
Mon is on east-west cut line burned timber to south burnt, clear cut to north.
Burned 9/2020
Compass decl. 14¼°E.
Oregon Coordinate Reference System
Cottage Grove - Canyonville Zone
N 203631.423 E 284819.661