

PRIMARY CORNER DESCRIPTION N NE Corner for Sec. 1

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by John A. McQuinn, Deputy Surveyor, under Contract #466, dated April 5, 1883 (DCSO records Vol. 8 Page(s) 3481)

-----  
Set post 4½ ft. long, 4" sq., 24" in ground for cor. to Tps. 24 and 25 S., Rgs. 1 and 2 W. marked T24S S31 on NE.; R1W S6 on SE.; T25S S1 on SW.; and R2W S36 on NW., faces with 6 notches on each edge, from which  
A Fir 14" dia., bears N.20°E., 16 lks. dist. mkd. T24S R1W S31 BT.  
A Fir 12" dia., bears S.60½°E., 22 lks. dist. mkd. T25S R1W S31 BT.  
A Fir 12" dia., bears S.63°W., 32 lks. dist. mkd. T25S R2W S1 BT.  
A Fir 14" dia., bears N.25°W., 15 lks. dist. mkd. T24S R2W S36 BT.

Fd. and used McQuinn's corner in GLO Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #619, dated June 5, 1893 - (DCSO records Vol. 7 Page(s) 2889-90)

GLO survey by Carl S. Nicklin, Deputy Surveyor, under contract #664 dated May 23, 1896 (DCSO records Vol. 7 Page(s) 2776¼)

-----  
This corner, which is a post 2" sq., 2 ft. above ground, marked and witnessed as described by the Surveyor General. I re-establish this cor. as follows:  
Set a Fir post 4 ft. long, 4' sq., 24" in the ground for cor. of T 24 and 25 S., R. 2 W., on W. bdy. of T24S R1W, marked: T24S R2W S36 on NW.; T25S R2W S1 on SW. faces; with 6 notches on N., W., and S. edges, from which  
A Fir 14" dia., bears N.16°W., 16 lks. dist. mkd. T24S R2W S36 BT.  
A Fir 14" dia., bears S.58°W., 33 lks. dist. mkd. T25S R2W S1 BT.  
This cor. is on a steep hillside sloping N. about 300 ft. below the closing cor. of Ts. 24 and 25 S., R 2 W.

BLM resurvey by Levi E. Tallett and C. Albert White, Cadastral Surveyors, under Group #294, Surveyed May 1951/Aug. 1963 - (DCSO records Vol. 32 Page(s) 13276)

-----  
"The intermediate corners along this line which were established by McQuinn formerly referred only to T. 24 S., R. 2 W. The purported retracement of the south boundary of sec. 31 and the reported establishment of closing corners on the  
(Cont. Next Page)

TOWNSHIP 25 RANGE 02 POINT IDENTIFIER # 666700

PRIMARY CORNER DESCRIPTION N NE Corner for Sec. 1

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

boundary by Hezekiah Johnson in 1900 **having proved to be fictitious**, the McQuinn corners except for the south  $\frac{1}{4}$  sec. cor. of sec.31 and the south  $\frac{1}{4}$  sec. cor. of sec. 36, are changed in 1963 to corners of maximum control in order to provide a basis for Consent Decree "Civil No. 60-135, Oregon."

The cor. of Tps. 24 and 25 S., R. 2 W., on the W. bdy. of Sec. 31, T24-1, determined at record distance from the original bearing trees:

A Fir 30" dia., bears N.27°E., 16 lks. dist., with blaze healed. (Rec. brg. N.20°E.)

A rotted stump bears S.56°E., 22 lks. dist. (Rec. brg. S.60 $\frac{1}{2}$ °E.)

A Fir 18" dia., bears S.57 $\frac{1}{2}$ °W., 32 lks. dist., with partial scribe marks visible on blaze under 68 years of overgrowth. (Rec. brg. S.63°W.)

At the corner point

Set an iron post 36" long, 3" dia., 8" in the ground to solid rock and in a mound of stone, 4 ft. base to top, with brass cap marked:

T 24 S	
R 2 W	T 24 S
<u>S 36</u>	R 1 W
S 1	S 31
T 25 S	

1951

from which bearing trees mkd. in 1851:

A Fir 18" dia., bears N.35 $\frac{1}{2}$ °W., 28 lks. dist. mkd. T24S R2W S36 BT.

A Fir 20" dia., bears S.44 $\frac{1}{2}$ °W., 46 lks. dist. mkd. T25S R2W S1 BT.