

TOWNSHIP 25 RANGE 02 POINT IDENTIFIER # 700100

PRIMARY CORNER DESCRIPTION SE Cor. Sec. 36 (SE Tsp. Cor.)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by John A. McQuinn, Deputy Surveyor, under Contract #466, dated April 5, 1883 (DCSO records Vol. 10 Page(s) 4069)

-----  
Set a Cedar post 4½ ft. long, 4" sq., 24" in the ground for corner to Tps. 25 and 26 S., R's 1 & 2 West, marked T25S S31 on NE.; R1W S6 on SE.; T26S S1 on SW.; and R2W S36 on NW. faces, with 6 notches on each edge, from which  
A Fir 30" dia., bears N.85°E., 116 lks. dist. mkd. T25S R1W S31 BT.  
A Pine 16" dia., bears S.55°E., 45 lks. dist. mkd. T26S R1W S6 BT.  
A Pine 16" dia., bears S.60°W., 66 lks. dist. mkd. T26S R2W S1 BT.  
A Fir 36" dia., bears N.68°W., 138 lks. dist. mkd. T25S R2W S36 BT.

Cor. tied in GL0 resurvey by Fred Mensch, Deputy Surveyor, under Contract #797, dated April 19, 1910 - (DCSO records Vol. 10 Page(s) 4083)

GL0 survey by C.M. Collier, Deputy Surveyor, under Special Instructions dated May 12, 1913 - (DCSO records Vol. 10 Page(s) 4266)

-----  
Intersect the point for the cor. of Tps. 25 and 26 S., R2W., located by reference to the bearing trees as described by the surveyor general; all traces of the cor. have disappeared. I re-establish this cor. in its original position, as follows:  
Set a basalt stone 14x10x6 ins., 9" in the ground, for cor. of Tps. 25 and 26 S., R2W., marked with 6 notches on the N. and W. edges, witnessed by the original bearing trees as follows:  
A Fir 30" dia., bears N.85°E., 116 lks. dist. Marks obliterated.  
A Pine 16" dia., bears S.55°E., 45 lks. dist. Marks obliterated.  
A Pine 16" dia., bears S.60°W., 66 lks. dist. mkd. T26S R2W S1 BT.  
A Fir 36" dia., bears N.68°W., 138 lks. dist. mkd. T25S R2W S36 BT.

Douglas County Surveyors Office - Vernon "Ray" Tracy and crew  
June 9, 1966 - C.S. File 52/77-16

-----  
Found - Orig. 16" now 30" Pine, S.60°W., 43.6 ft. scribe visible, on prev. opened scar. (Cont. Next Page)

TOWNSHIP 25 RANGE 02 POINT IDENTIFIER # 700100

PRIMARY CORNER DESCRIPTION SE Cor. Sec. 36 (SE Tsp. Cor.)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Orig. 16" now 30" Pine, S.55°E., 29.7 ft., shows old scar, recorded as marks obliterated.  
Orig. 30" now 40" Fir, N.85°E., 76.6 ft., shows fragmentary bark scribe, recorded as being obliterated. NW. BT gone.  
Do not find stone as called for.  
Set Brass cap at cor. mkd: County Surveyors Office  
T25S R2W S 36 | R1W  
T26S S 1  
1966  
New BTs- 7" D.Fir N.56°W., 28.2 ft. mkd. T25S R2W S36 CS BT.  
15" Hemlock S.50°W., 8.1 ft. mkd. T26S R2W S1 CS BT.  
Corner lies on NE. slope in mound of stone 12" high.

BLM Dependent Resurvey by A Bert Skeesick, Cadastral Surveyor Under Group No. 2317, Surveyed June 2010/June 2011 - DCSO records Vol. 57 Page(s) 22781-2

-----

The cor. of Tps. 25 & 26 S., R. 2 W., monumented with an iron post, 2" dia., firmly set, projecting 4" above a mound of stone, 2 ft. base, 1 ft. high, with brass cap (properly) mkd. from which the remains of the orig. BTs reported by Collier

- A fir, 47" dia., bears S.87¼°E., 76.6 ft., with no marks visible. (Record, N.85°E.)
- A pine, 37" dia., bears S.44°E., 29.7 ft., with no marks visible. (Record, S.55°E.)
- A pine snag, 35" dia., bears S.60°W., 43.6 ft., with a healed blaze.

and bearing trees mkd. by the Douglas County Surveyor's Office in 1966

- A hemlock, 31" dia., bears S.51¼°W., 7.9 ft., with a healed blaze.
- A fir, 11" dia., bears N.57¾°W., 27.2 ft., with a healed blaze.

BLM dependent resurvey by Jeffrey O. Covington, Cadastral Surveyor, under Group No. 2923, surveyed July 2018/March 2020- (DCSO records Vol. 59 Pages 24046)

-----

The cor. of T25 & 26S, R2W, reported by Skeesick in 2010-11, monumented with an iron post, 1¼" dia. (Record, 2" dia.), firmly set, projecting 16" above ground, in a mound of stone, 2 ft. base, 12". high, with a brass cap (properly) mkd. from which the remains of the BTs reported by Skeesick

- A fir, 45" dia., bears S.87¼°E., 76.6 ft., no marks visible. (Original)
- A pine snag, 37" dia., bears S.44°E., 29.7 ft., no marks visible. (Original)

Continued next page

TOWNSHIP 25 RANGE 02 POINT IDENTIFIER # 700100

PRIMARY CORNER DESCRIPTION SE Cor. Sec. 36 (SE Tsp. Cor.)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A hemlock, 32" dia., bears S.51 $\frac{3}{4}$ °W., 7.9 ft., with a healed blaze.  
A pine snag, 35" dia., bears S.60°W., 43.6 ft., with a healed blaze. (Original)  
A fir, 12" dia., bears N.57 $\frac{3}{4}$ °W., 27.2 ft., with a healed blaze.