

TOWNSHIP 25 RANGE 02 POINT IDENTIFIER # 700133

PRIMARY CORNER DESCRIPTION CC to S. 31, T25-1; & S. 6, T26-1

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO Survey by Hezekiah H. Johnson, U.S. Deputy Surveyor, under Contract #721, dated May 1, 1900 - (DCSO records Vol. 8 Page(s) 3506)

Intersect the W. bdy. of Tp. (25-1), 6.75 chs. S. of the ¼ sec. cor. on the E. bdy. of Sec. 36, T25S R2W, and at the point of intersection, I set a basalt stone 18x11x6 ins., 12" in the ground for closing cor. of secs. 6 and 31, marked C C., with 6 notches on the N. and S. edges, from which
A Fir 24" dia., bears N.58°E., 63 lks. dist. mkd. CC T25S R1W S31 BT.
A Fir 6" dia., bears S.71°E., 45 lks. dist. mkd. CC T26S R1W S6 BT.

Fd. and used in GLO resurvey by Fred Mensch, Deputy Surveyor, under Contract #797, dated April 19, 1910 - (DCSO records Vol. 9 Page(s) 3577)

Douglas County Surveyors Office - Vernon "Ray" Tracy and crew May 31, 1967 - C.S. File 52/30-86

Found - Orig. Corner stone, 17x14x7", set in mound of stone and marked "CC" and 6 notches on N. and S.
Orig. 24" now 33" Fir, N.58°E., 41.6 ft., alive, shows good scar. Do not open.
Orig. 6" now 21" Fir, S.71°E., 29.7 ft., alive, shows good scar. Do not open. Rescribed "CC T26S R1W S6 CS BT"
Set brass cap in mound of stone mkd: County Surveyors office
R2W CC | S 31 T25S R1W
 | S 6 T26S
 1967
New BT - 10" D.Fir N.37°E., 17.3 ft. mkd. CC T25S R1W S31 CS BT.
Corner lies approx. 100 ft. S. of creek, course SE.