

PRIMARY CORNER DESCRIPTION E. 1/4 Cor. for Sec. 36 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by John A. McQuinn, Deputy Surveyor, under Contract #466, dated April 5, 1883 (DCSO records Vol. 8 Page(s) 3475)

Set post 3 ft. long, 3" sq., 24" in the ground for 1/4 sec. cor. mkd. 1/4 S. on W. face, from which
A Fir 24" dia., bears S.70°E., 48 lks. dist. mkd. 1/4 S BT.
A Hemlock 24" dia., bears N.71°W. 17 lks. dist. mkd. 1/4 S BT.

GLO resurvey by Hezekiah H. Johnson, Deputy Surveyor, under Contract #721, dated May 1, 1900 - (DCSO records Vol. 8 Page(s) 3492 and 3493)

(Page 3492)
I am unable to find any trace of the 1/4 sec. cor.
(Page 3493)
Set a Fir post 3 ft. long, 3" sq., 24" in the ground for 1/4 sec. cor. bet. secs. 31 and 36, marked 1/4 S36 on W. face and S31 on E. face, from which
A Fir 14" dia., bears S.88°E., 22 lks. dist. mkd. 1/4 S31 BT
A Hemlock 6" dia., bears S.55°W., 22 lks. dist. mkd. 1/4 S36 BT.

Douglas County Surveyors Office - Vernon "Ray" Tracy and crew May 1967 - C.S. File 52/30-85

Found - Orig. 6" now 10" Hemlock, S.55°W., 14.5 ft., alive & chopped open showing "1/4 S36" scribe & unopened lower scar.
Orig. 14" Fir, now down and badly decayed, S.88°E., 14.5 ft., find edge of old axe face.
Set Brass cap at cor. mkd: County Surveyors Office
T 25 S
R2W 1/4 S 36 | R1W
1967 |
New BTs- 17" Hemlock S.47°W., 35.7 ft. mkd. 1/4 S36 CS BT.
8" Hemlock N.46°W., 20.8 ft. mkd. 1/4 S36 CS BT.
Corner lies 50 ft. E. of creek, course S.

Glen McChesney, for Weyerhaeuser Co. - Labor Day, 1975 (Filed Dec. 1980) - C.S. File 58/8-43

Found - No trace of orig. Fir post, 1900.
6" now 10" Hemlock scribing visible, bears S.55°W., 14.5 ft. center measurement.
1967 County Brass cap.
(Cont. Next Page)

TOWNSHIP 25 RANGE 02 POINT IDENTIFIER # 700140

PRIMARY CORNER DESCRIPTION E. 1/4 Cor. for Sec. 36 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

18" Hemlock, scribing visible, bears S.47°W., 35.7 ft. center measurement.
8" dead Hemlock, scribing visible, bears N.46°W., 20.8 ft. center measurement.
Accessories added this date:
48" Fir N.15°W., 17.8 ft. with W nail and plate.
48" Red Cedar S.51°W., 37.3 ft. with W nail & plate.
(CC for Sec. 31, T25-1 and S6, T26-1 approx. 401 ft. South and 2 ft. East.)