

PRIMARY CORNER DESCRIPTION Sec. Cor. for 25 & 36 only (East)

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GL0 survey by John A. McQuinn, Deputy Surveyor, under Contract #466, dated April 5, 1883 (DCSO records Vol. 8 Page(s) 3475-76)

Set post 4½ ft. long, 4" sq., 24" in ground for cor. to secs. 25, 30, 31 and 36, marked T25S S30 on NE.; R1W S31 on SE.; R2W S36 on SW.; and S25 on NW. faces, with 5 notches on N. and 1 notch on S. edges, from which
A Fir 18" dia., bears N.40°E., 15 lks. dist. mkd. T25S R1W S30 BT.
A Fir 18" dia., bears S.44°E., 33 lks. dist. mkd. T25S R1W S31 BT.
A Fir 22" dia., bears S.28°W., 46 lks. dist. mkd. T25S R2W S36 BT.
A Fir 12" dia., bears N.61°W., 16 lks. dist. mkd. T25S R2W S25 BT.

GL0 survey by Hezekiah H. Johnson, Deputy Surveyor, under Contract #721, dated May 1, 1900 - (DCSO records Vol. 8 Page(s) 3492 and 3493-94)

(Page 3492)
No trace of the cor. of secs. 25, 30, 31 and 36 can be found. (Pgs. 3493-94)
A Hemlock 6" dia. for cor. of secs. 25, 30, 31 and 36, I mark T25S S30 on NE.; R1W S31 on SE.; S36 on SW. and R2W S25 on NW. sides, with 5 notches on N. and 1 notch on S. sides, from which
A Hemlock 6" dia., bears N.29°E., 26 lks. dist. mkd. T25S R1W S30 BT.
A Fir 30" dia., bears S.26°E., 31 lks. dist. mkd. T25S R1W S31 BT.
A Fir 6" dia., bears S.25°W., 65 lks. dist. mkd. T25S R2W S36 BT.
A Fir 6" dia., bears N.35°30'W., 27 lks. dist. mkd. T25S R2W S25 BT.

Glen McChesney - For: Weyerhaeuser Co. - June 2, 1959 - C.S. File 53/112-48

Found - Orig. 6" Hemlock corner tree, now 12", old face, squared.
8" Hemlock, N.29°E., 26 lks. (17.2 ft.), rotten remains, down Hemlock, marks should have been obliterated by 1900 survey.
36" Fir, S.26°E., 31 lks. (20.5 ft.), now 44", face not opened. Marks should have been obliterated by 1900 survey. (Cont. Next Page)

TOWNSHIP 25 RANGE 02 POINT IDENTIFIER # 700200

PRIMARY CORNER DESCRIPTION Sec. Cor. for 25 & 36 only (East)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

4" now 6" Fir, S.25°W., 65 lks. (42.0 ft.), scribing visible.
6" now 8" Fir, N.35½°W., 27 lks. (17.8 ft.), scribing visible.
Hosford identified the above corner tree and all BTs.
Accessories added this date;
44" Fir, S.28°W., 43.0 ft. "W" nail and plate.
42" Fir N.68°W., 40.0 ft. "W" nail and plate.

Douglas County Surveyors Office - Vernon "Ray" Tracy and crew
May 5, 1967 - C.S. File 52/30-87

Found - Orig. Corner tree, 6" now 17" Hemlock, showing faint scars.
Orig. 30" now 48" Fir, S.26°E., 20.5 ft., alive, shows good scar.
Orig. 6" now 8" Fir S.25°W., 42.9 ft., alive, scribe marks visible on unhealed blaze.
Orig. 6" now 10" Fir N.35½°W., 17.8 ft., alive, scribe marks visible on unhealed blaze.
Orig. NE. BT gone.
Set 3/4" Iron rod on W. side and at base of corner tree, 1 ft. from center.
New BT - 8" W.Fir S.43°W., 29.3 ft. mkd. T25S R2W S36 CS BT.
Corner lies 175 ft. South of old scarred man Jeep road at cutting corner, logged to NW.

BLM Resurvey by James E. Jelley, Cadastral Surveyor, under Group #350 and 929, surveyed May 1978/May 1980 - (DCSO records Vol. 42 Page(s) 16328)

At the cor. Of secs. 25 & 36 only, perpetuated and recorded by Tracy in 1967, and further perpetuated and recorded by Thomas Shrum, Jr. in 1975 monumented with an iron post, 1½" dia., firmly set, projecting 10" above ground with brass cap mkd:
T25S R2W
S 25 |
S 36 | WM
1975
from which BTs mkd. by Johnson
A fir, 50" dia., bears S.26°E., 31 lks. with healed blaze.
A W.fir, 8" dia., bears S.25°W., 65 lks., with healed blaze.
A W.fir, 8" dia. bears N.35½°W., 31½ lks with scribe marks
T25S R2W S25 BT visible on opened blaze (rec 27 lks)
and BT by Tracy
A W.fir, 8" dia., bears S.43°W., 46 lks., with scribe R2W
S36 BT visible on open blaze. _____ Cont. next pg

TOWNSHIP 25 RANGE 02 POINT IDENTIFIER # 700200

PRIMARY CORNER DESCRIPTION Sec. Cor. for 25 & 36 only (East)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Survey by Glenn Baughman - For: Weyerhaeuser Co. - Aug. 1975
(filed June 1979) - M 77-57

Found - 56" Fir, face grown over, bears S.26°E., 20.5 ft.
Original BT.
17" Hemlock with visible scribe. (down) Orig. BT.
8" Fir bears S.25°W., 42.9 ft., Orig. BT.
10" Fir bears S.43°W., 30.3 ft. (DCSO BT.)
10" Fir bears N.48°W., 20.5 ft.
All trees previously opened, scribes still visible.
SET Brass cap.

Fd. & used on BLM resurvey by A. Bert Skeesick, Cadastral
Surveyor under Group #1979, surveyed 2001/2002- (DCSO rec.
Vol. 54 Page(s) 20900-1)

Douglas Co. Surveyors Office - Crew: Stephen Flause & Jeff
Lorsung- 3/30/2022 (Filed 7/21/2022) - C.S. File 67/52-30

Found - 2½" brass cap (properly mkd) on I. Pipe proj. 6"
Orig. BT
Burnt 57" Fir S.22°E. 19.6 ft (rec. S.26°E. 19.5 ft)
DCSO BT 1967
28"x2' sawn burnt stump S.45°W., 30.2 ft. (rec
S.43°W., 30.3 ft) PK top center.
Baughman BT
29" double trunk Hemlock (rec 10" Fir) N.43½°W.,
20.8 ft. (rec. N.48°W., 20.5 ft) brass washer
added in face. PK nail right side center.
New - Burnt-dead 45" Fir N.34°E., 50.7 ft. Brass washer n
old face, PK nail right side center.
Note - Area burnt 9/2020
Compass decl. 14½°E.
See sketch in file.
Lat: Lat: 43°21'27.99"N Long: 122°52'25.49"W