

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Hezekiah H. Johnson, Deputy Surveyor, under Contract #721, dated May 1, 1900 - (DCSO records Vol. 9 Page(s) 3556)

Intersect W. bdy. of Tp., (T25-1) 6.80 chs. S. of the ¼ sec. cor., on the E. bdy. of sec. 25, T25S R2W., at at point of intersection, I set a basalt stone, 18x10x6 ins., 12" in the ground for closing cor. of secs. 30 and 31, marked C C with 1 notch on S. and 5 notches on N. edges, from which
A Cedar 12" dia., bears N.62½°E., 45 lks. dist. mkd. CC T25S R1W S30 BT.
A Fir 20" dia., bears S.51°E., 40 lks. dist. mkd. C C T25S R1W S31 BT.

V.W. Hosford, O.L.S. #253 - April 1949/Oct. 1950 - C.S. File 40/279 and M 12-61

Closing cor. 30 - 31, T25S R1W bears East 46.2 ft.
As this closing corner is not the legal terminus of the closing line, therefore at this point, I set a 1" I.P. with steel cap from which
A Hemlock 8" dia., bears N.44°E., 18.8 ft. mkd. T25S R1W S30 C C P.S. 253 BT.
A Cedar 24" dia., bears S.36°E., 32.0 ft. mkd. T25S R1W S31 C C P.S. 253 BT.

BLM Resurvey by James E. Jelley, Cadastral Surveyor, under Group #350 and 929, Surveyed May 1978/May 1980 - (DCSO records Vol. 42 Page(s) 16328-29)

(35.15 chs.)
A point established and recorded by Hosford, in 1950, monumented with an iron pipe, 1" dia., firmly set, projecting 5" above ground, with steel plate, 2' sq., welded on top, mkd. in 1950, from which bearing trees mkd. by Hosford:
A Hemlock 14" dia., bears N.43¼°E., 30 lks. dist., with scribe marks 25 R1W S30 CC PS 253 BT visible on open blaze.
A Cedar 26" dia., bears S.36¼°E., 49½ lks. dist. with scribe marks 25S R1W S31 CC PS 253 BT visible on open blaze.
(35.23 chs., N.0°12'W.)
From this point, the original closing cor. of secs. 30 and 31, T25S R1W bears East, 0.665 chs. dist., determined at record bearing and distance from the remains of the original bearing trees:
(Cont. Next Page)

PRIMARY CORNER DESCRIPTION C C for Secs. 30 & 31 only, T25-1

Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____

A sawed Cedar stump 18" dia., bears N.62½°E., 45 lks. dist., with scribe marks T25S R1W S30 BT visible on open blaze.

A Fir snag 22' dia., bears S.51°E., 40 lks. dist., with scribe marks T25S R1W S31 BT visible on open blaze.

James Artman, LS #2268 - For: U.S. Forest Service - 1990 - C.S. 63/124-6

 Found - 1¼" Iron pipe 5" above ground with stone mound.
 18" Hemlock bears N.43°15'E., 18.8 ft. partial scribing visible.
 28" Cedar S.36°E., 32.0 ft. partial scribing vis.
 34" Cedar stump (Orig. CC BT) bears N.82°E., 74.0 ft. to face, partial scribing visible. Stump is a triple trunked tree stump, bearings and distance is the trunk stump most southwesterly (approx. 16" in diameter)
 20" W.Fir snag (Orig. CC BT) bears S.76°45'E., 68.3 ft. to face, partial scribing visible.

Set 2" galv. Iron pipe 30" in length, 25" in the ground with a 3" brass cap in a 36" dia. rock mound, cap marked:

```

      R      T 25 S      R
      2          S 30      1
      W  S 25  |-----CC W
                S 31
      RLS 2268      1990
    
```

BLM resurvey by A. Bert Skeesick, Cadastral Surveyor under Group #1979, surveyed 2001/2002- (DCSO rec. Vol. 54 Page(s) 20901-2)

 The true closing cor. of secs. 30 & 31, T25S R1W, established by Hosford, in 1950, shown on Plat of Survey by Larry J. Friar, remonumented by Artman, in 1990, monumented with an iron post, 2" dia., firmly set in a collar of stone, 2 ft. dia. to top, with brass cap (properly) mkd.

from which bearing trees mkd. by Hosford & reported by Jelley

A hemlock, 22" dia., bears N.43½°E., 18.6 ft., with fragmentary scribe marks visible on partially healed blaze. (Record, 19.8 ft.)

A cedar, 32" dia., bears S.36¼°E., 32.7 ft., with fragmentary scribe marks visible on partially healed blaze.

From this point, the orig. closing cor. of secs. 30 & 31, T25S R1W, bears N.89°04'05"E., 47.29 ft., (record, East, 43.9 ft.) determined at record from the remains of the original bearing trees

continued next page

TOWNSHIP 25 RANGE 02 POINT IDENTIFIER # 700233

PRIMARY CORNER DESCRIPTION C C for Secs. 30 & 31 only, T25-1

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A sawed cedar stump, 19" dia., bears N.60½°E., 29.7 ft., with scribe marks BT visible on partially healed blaze. (Record, N.62½°E.)

A roothole, bears S.62°E., 26.4 ft., with decayed fir stump lying alongside, with fragmentary scribe marks visible on open blaze. (Record, S.51°E.)