

PRIMARY CORNER DESCRIPTION Sec. Cor. for 24 & 25 only (East)

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by John A McQuinn, Deputy Surveyor, under Contract #466, dated April 5, 1883 (DCSO records Vol. 8 Pg 3976-77)

Set post 4½ ft. long, 4" sq., 24" in ground for cor. to secs. 19, 24, 25 and 30, marked T25S S19 on NE.; R1W S30 on SE.; S25 on SW.; and R2W S24 on NW. faces, with 4 notches on N. and 2 notches on S. edges, from which

- A Hemlock 8" dia., bears S.85°E., 19 lks. dist. mkd. T25S R1W S30 BT.
- A Cedar 18" dia., bears N.84°W., 16 lks. dist. mkd. T25S R2W S24 BT.
- A Hemlock 12" dia., bears N.35°E., 12 lks. dist. mkd. T25S R1W S19 BT.
- A Hemlock 24" dia., bears S.74°W., 35 lks. dist. mkd. T25S R2W S25 BT.

GLO survey by Hezekiah H. Johnson, Deputy Surveyor, under Contract #721, dated May 1, 1900 - (DCSO records Vol. 8 Page(s) 3493 and 3495)

(Page 3493) - Find no trace of any line or corners.
(Page 3495)

Set a basalt stone 17x11x8 ins., 12" in the ground for cor. of secs. 19, 24, 25, and 30, marked with 4 notches on N. and 2 notches on S. edges, from which

- A Hemlock 4" dia., bears N.21°E., 16 lks. dist. mkd. T25S R1W S19 BT.
- A Hemlock 5" dia., bears S.48°E., 29 lks. dist. mkd. T25S R1W S30 BT.
- A Fir 12" dia., bears S.32°W., 60 lks. dist. mkd. T25S R2W S25 BT.
- A Cedar 6" dia., bears N.24°W., 68 lks. dist. mkd. T25S R2W S24 BT.

V. W. Hosford, O.L.S. #253 - April 1949/Oct. 1950 - C.S. File 40/279 and M 12-61

I set a 1½" I.P. with steel cap, from which

- A Fir 32" dia., bears S.78½°W., 35.9 ft. mkd. T25S R2W S25 P.S. 253 BT.
- A Fir 30" dia., bears N.39°W., 16.4 ft. mkd. T25S R2W S24 P.S. 253 BT.

Glen McChesney - For: Weyerhaeuser - 7/30/1958 - C.S. 53/112-35

Hosford's corner found OK. Added "W" nails and plates to Hosford BTs.

cont.

