

PRIMARY CORNER DESCRIPTION E. 1/4 Cor. for Sec. 24 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by John A. McQuinn, Deputy Surveyor, under Contract #466, dated April 5, 1883 (DCSO records Vol. 8 Page(s) 3477)

Set post 3 ft. long, 3" sq., 24" in ground for ¼ sec. cor. mkd. ¼ S on W. face, from which
A Dogwood 5" dia., bears N.71°E., 21 lks. dist. mkd. ¼ S BT.
A Fir 8" dia., bears S.24°W., 10 lks. dist. mkd. ¼ S BT.

GLO survey by Hezekiah H. Johnson, Deputy Surveyor, under Contract #721, dated May 1, 1900 - (DCSO records Vol. 8 Page(s) 3493 and 3495-96)

(Page 3493)
Find no trace of any line or corners.
(page 3495-96)
Set a basalt stone 15x10x6 in., 10" in the ground for ¼ sec. cor. mkd. ¼ on W. face, from which
A Fir 6" dia., bears S.41°E., 36 lks. dist. mkd. ¼ S19 BT.
A Fir 7" dia., bears S.75°W., 52 lks. dist. mkd. ¼ S24 BT.

V.W. Hosford, Surveyor - May 1949/Oct. 1950 - C.S. File 40/279

I Set a 1½" I.P. with steel cap, from which
A Fir 32" dia., bears S.57°W., 14.6 ft. mkd. T25S R2W ¼ S24 P.S. 253 BT.
A Fir 24" dia., bears N.27°W., 19.0 ft. mkd. T25S R2W ¼ S24 P.S. 253 BT.

BLM resurvey by James E. Jelley, Cadastral Surveyor, under Group #'s 350 and 929 - Surveyed May 1978/May 1980 - (DCSO records Vol. 42 Page(s) 16331)

The ¼ sec. cor., reestablished at proportionate distance and recorded by Hosford in 1950, and is accepted as the best available evidence of the position of the original corner, monumented with an iron pipe, 1" dia., firmly set, projecting 10" above ground, with a steel plate, 2" square, welded on top, from which the remains of bearing trees mkd. by Hosford:
A sawed Fir stump, 32" dia., bears S.57°W., 25½ lks. dist., no marks visible on bark blaze.
A sawed Fir stump 28" dia., bears N.27°W., 30 lks. dist., with scribe marks BT visible on open blaze.
No new suitable trees available.

continued next page

TOWNSHIP 25 RANGE 02 POINT IDENTIFIER # 700340

PRIMARY CORNER DESCRIPTION E. 1/4 Cor. for Sec. 24 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Rob Ward - For: Seneca Jones Timber Co. - Aug. 2003 - M142-79

Found - 2" Iron pipe with 2¼" iron cap marked with center
punch only with the following accessories:

32" D.Fir stump bears S.57°W., 16.8' (healed face)

28" D.Fir stump bears N.27°W., 19.8' (scribing vis.)

New BTs- 7" D.Fir bears S.78°W., 12.0' blazed, scribed "¼ S24
BT"

5" D.Fir bears S.6°W., 10.1' blazed, scribed "¼ S24
BT"