

TOWNSHIP 25 RANGE 02 POINT IDENTIFIER # 700373

PRIMARY CORNER DESCRIPTION W. 1/4 Cor. for Sec. 19 only, T25-1

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

V.W. Hosford, O.L.S. #253 - April 1949/Oct. 1950 - C.S. file 40/279 and M 12-61

-----  
I set a 1½" I.Pipe with steel cap, from which  
A Cedar 30" dia., bears N.32°E., 20.7 ft. mkd. T25S R1W ¼  
S19 P.S. 253 BT.

BLM resurvey by James E. Jelley, Cadastral Surveyor, under Group #'s 350 and 929 - Surveyed May 1978/May 1980 - (DCSO records Vol. 42 Page(s) 16331-32)

-----  
Point for the ¼ sec. cor. of sec. 19 only, T25S R1W, determined at midpoint latitudinally on the W. bdy. of the sec.

Set a brass tablet, 3¼" dia., 3½" stem in drill hole, in solid rock creek bottom, with top mkd.

	T 25 S
	¼ S 19
	R 1 W
	1978

from which the remains of a bearing tree of which I have no record

A Cedar snag 18" dia., bears N.71½°E., 64½ lks. dist., with fragmentary scribe marks visible on open blaze.

and a new bearing tree and bearing object

A Fir 5" dia., bears S.76 ¾°E., 68½ lks. dist. mkd. ¼  
S19 BT.

Exposed bedrock, bears S.57 ¾°W., 6½ lks. dist. mkd. X  
BO.

No accessory available in NE. quadrant.

Found OK by R. Rice, Aug. 2003 - M142-79