

PRIMARY CORNER DESCRIPTION Sec. Cor. for 13 & 24 only (East)

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

GL0 survey by John A. McQuinn, Deputy Surveyor, under Contract #466, dated April 5, 1883 (DCSO records Vol. 8 Page(s) 3478)

Set post 4½ ft. long, 4" sq., 24" in ground for cor. to secs. 13, 18, 19 and 24, marked T25S S18 on NE.; R1W S19 on SE.; R2W S24 on SW.; and S13 on NW. faces, with 3 notches on N. and S. edges, from which

- An Alder 12" dia., bears N.73°E., 82 lks. dist. mkd. T25S R1W S18 BT.
- A Hemlock 24" dia., bears S.30°E., 10 lks. dist. mkd. T25S R1W S19 BT.
- A Maple 36" dia., bears S.44°W., 45 lks. dist. mkd. T25S R2W S24 BT.
- A Maple 24" dia., bears N.55°W., 11 lks. dist. mkd. T25S R2W S13 BT.

GL0 survey by Hezekiah H. Johnson, Deputy Surveyor, under Contract #721, dated May 1, 1900 - (DCSO records Vol. 8 Page(s) 3493 and 3496)

(Page 3493)
Find no trace of any line or corners.
(Page 3496)

Set a basalt stone 14x10x7 ins., 10" in the ground for cor. of secs. 13, 18, 19 and 24, marked with 3 notches on N. and S. edges, from which

- A Fir 20" dia., bears N.20°E., 61 lks. dist. mkd. T25S R1W S18 BT.
- A Fir 5" dia., bears S.49°E., 30 lks. dist. mkd. T25S R1W S19 BT.
- A Fir 8" dia., bears S.70°W., 24 lks. dist. mkd. T25S R2W S24 BT.
- A Hemlock 4" dia., bears N.32°W., 15 lks dist. mkd. T25S R2W S13 BT.

V. W. Hosford, Surveyor - May 1949/Oct. 1950 - C.S. File 40/279 and M 12-61

I set a 2" I.Pipe with steel cap, from which
A Hemlock 10" dia., bears S.58½°W., 12.0 ft. mkd. T25S R2W S24 P.S. 253 BT.
A Fir 30" dia., bears N.36°W., 21.2 ft. mkd. T25S R2W S13 P.S. 253 BT.

(Cont. Next Page)

TOWNSHIP 25 RANGE 02 POINT IDENTIFIER # 700400

PRIMARY CORNER DESCRIPTION Sec. Cor. for 13 & 24 only (East)

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

V.W. Hosford, Surveyor - Sept. 1957 - C.S. File 42/308-12

At this corner, I found the iron pipe with steel cap set in my survey of 1950. The BT for sec. 13 has been cut. The stump still shows the old faces, but all scribing has burned away. The BT for sec. 24 is up-rooted and badly burned. This area has burned extensively and no green trees remain within a reasonable distance. From my original I.P. corner:
A Fir stump 30" dia., bears N.36°W., 21.2 ft. mkd. T25S R2W S13 253 BT. (My original re-marked)
A dead Fir 40" dia., bears S.9½°W., 64.8 ft. mkd. T25S R2W S24 253 BT.

BLM resurvey by James E. Jelley, Cadastral Surveyor, under Group #'s 350 and 929 - Surveyed May 1978/May 1980 - (DCSO records Vol. 42 Page(s) 16332)

The sec. cor., reestablished at proportionate distance and recorded by Hosford in 1950, and is accepted as the best available evidence of the position of the original corner, monumented with an iron pipe, 1" dia., loosely set, projecting 16" above ground, with a steel plate, 2" sq., welded on top, from which the remains of BTs mkd. by Hosford:
A sawed Fir stump 25" dia., bears N.34½°W., 29 lks. dist. with scribe marks T25S R2W S13 PS 253 BT visible on open blaze.
A Fir snag 40" dia., bears S.11¼°W., 105 lks. dist., with scribe marks T25S R2W S24 PS 253 BT visible on open blaze.

At the corner point
Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:

T 25 S	T 25 S
S 13	S 19
S 24	R 1 W
R 2 W	
	1978

from which new bearing trees:
A Fir 9" dia., bears S.32½°W., 9½ lks. dist. mkd. T25S R2W S24 BT.
A Fir 5" dia., bears N.21 3/4°W., 23 lks. dist. mkd. T25S R2W S13 BT.
Reset iron pipe alongside iron post.

Found OK by R. Rice, Aug. 2003 - M142-79

continued next page

TOWNSHIP 25 RANGE 02 POINT IDENTIFIER # 700400

PRIMARY CORNER DESCRIPTION Sec. Cor. for 13 & 24 only (East)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM resurvey by A. Bert Skeesick, Cadastral Surveyor under Group #1979, surveyed 2001/2002- (DCSO rec. Vol. 54 Page(s) 20903-4)

The cor. of secs. 13 & 24 only, on the E. bdy. of the Tp., monumented with an iron post, 2½" dia., firmly set, projecting 4" above ground, in a mound of stone, 3 ft. base, 1 ft. high, with brass cap (properly) mkd.

from which the remains of a bearing tree mkd. by Hosford, in 1950 and 1957, and reported by Jelley

A sawed fir stump, 28" dia., bears N.34½°W., 19.1 ft., with scribe marks T25S R2W S13 253 BT visible on open blaze.

and bearing trees mkd. by Jelley

A fir, 16" dia., bears S.27°W., 5.6 ft. dist., with healed blaze. (Record, S.32½°W., 6.3 ft.)

A fir, 11" dia., bears N.21¾°W., 15.2 ft., with healed blaze.