

PRIMARY CORNER DESCRIPTION C C for Secs. 18 & 19 only, T25-1

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Hezekiah H. Johnson, Deputy Surveyor, under Contract #721, dated May 1, 1900 - (DCSO records Vol. 9 Page(s) 3562-63)

Intersect the W. bdy. of tp., (T25S R1W) 6.70 chs. S. of the ¼ sec. cor., on the E. bdy. of sec. 13, T25S R2W, and at the point of intersection, I Set a basalt stone 16x8x6 ins., 11" in the ground for closing cor. of secs. 18 and 19, mkd. C C with 3 notches on N. and S. edges, from which
A Cedar 26" dia., bears N.52°E., 29 lks. dist. mkd. CC T25S R1W S18 BT.
A Hemlock 34" dia., bears S.43°E., 62 lks. dist. mkd. CC T25S R1W S19 BT.

V. W. Hosford, Surveyor - May 1949/Oct. 1950 - C.S. File 40/279 and M 12-61

As this closing corner is not the legal terminus of the closing line, therefore at this point, I set a 2" I.P. with steel cap, from which
A Cedar 30" dia., bears N.81½°E., 53.5 ft. mkd. T25S R1W S18 CC P.S. 253 BT.
A Hemlock 20" dia., bears S.70°E., 13.2 ft. mkd. T25S R1W S19 CC P.S. 253 BT.

Douglas County Surveyors Office - V.R.Tracy - May 1967 -

Looked for, not found.

BLM resurvey by James E. Jelley, Cadastral Surveyor, under Group #'s 350 and 929 - Surveyed May 1978/May 1980 - (DCSO records Vol. 42 Page(s) 16333)

Point for the closing cor. of secs. 18 and 19, T25S R1W, at proportionate distance; there is no remaining evidence of the original corner.
Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:
T 25 S*T 25 S
S 13*S 18
R 2 W*S 19 CC
*R 1 W
from which 1978
A Fir 6" dia., bears N.71½°E., 10 lks. dist. mkd. T25S R1W S18 CC BT.
A Fir 6" dia., bears S.39¼°E., 20½ lks. dist. mkd. T25S R1W S19 CC BT.

continued next page

TOWNSHIP 25 RANGE 02 POINT IDENTIFIER # 700433

PRIMARY CORNER DESCRIPTION C C for Secs. 18 & 19 only, T25-1

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Found OK by R. Rice, Aug. 2003 - M142-79
Fd. & used on BLM resurvey by A. Bert Skeesick, Cadastral Surveyor under Group #1979, surveyed 2001/2002- (DCSO rec. Vol. 54 Page(s) 20905)
Ron Rice - For: Seneca Jones Timber Co. & Roseburg Resources Co. - Aug. 2012 - C.S. File 65/75-9 ----- Found - 3¼" BLM brass cap dated 1978 with the following accessories: 9" D.Fir bears N.68¼°E., 6.6' - healed face. 10" D.Fir bears S.44¼°E., 13.5' - healed face.