



TOWNSHIP 25 RANGE 02 POINT IDENTIFIER # 700540

PRIMARY CORNER DESCRIPTION E. 1/4 Cor. for Sec. 12 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A Fir 10" dia., bears S.7°W., 20 lks. dist. mkd. ¼ S12 BT.  
Bury the original corner stone alongside the iron post.

Glen McChesney - For; Weyerhaeuser Co. - Feb. 24, 1975 - C.S.  
File 59/11-6

-----  
Found - Brass cap. No trace of original stone.  
12" I.Cedar, N.20°W., 32.3', face healed over, with  
DCSO BT plate.  
10" Fir, S.7°W., 13.2 scribing visible on low face.  
DCSO BT plate.  
Hosford's steel cap. (cap brs S. 8.2 ft. from GLO BC)  
16" Fir, S.23°W., 9.1 ft. scribing visible.  
24" Fir N.34°W., 22.0 ft., face healed over. center  
of tree measurement.  
Accessories added this date:  
36" Fir, S.36°W., 35.4 ft. with "W" nail and plate.  
24" Fir, N.52°W., 14.2 ft. with "W" nail and plate.  
(These references are to the GLO brass cap.)

BLM resurvey by James E. Jelley, Cadastral Surveyor, under  
Group #'s 350 and 929 - Surveyed May 1978/May 1980 - (DCSO  
records Vol. 42 Page(s) 16336)

-----  
Fd 1951 BC from which the remains of BTs mkd by Tallet  
A sawed Fir stump 14" dia., bears S.7°W., 20 lks. dist.  
with axe marks visible on open blaze.  
A Cedar 9" dia., bears N.20°W., 49 lks. dist healed blaze.  
and bearing trees mkd. by Hosford in 1950:  
A Fir 18" dia., bears S.11 3/4°W., 27½ lks. dist. with  
fragmentary scribe marks visible on open blaze.  
A Fir 26" dia., bears N.50½°W., 23½ lks. dist., with  
healed blaze.

Steven Ness, L.S. #811 - For: Weyerhaeuser Co. - 10/ 1995 -  
M 123-3 A&B

-----  
Found 2½" GLO brass cap on 1" iron post, from which  
14" D.Fir broken stump, S.6°13'W., 13.8. No marks visible.  
(S.7°W., 13.2)  
20" D.Fir, S.11°30'W., 17.5. Large healed face (S.13°W.,  
17.7' from GLO monument)  
29" D.Fir snag, N.51°42'W., 16.0' to center. 14.0 to "W"  
nail. Face healed. "W" nail in small low blaze  
(N.52°W., 16.4 to center. 14.2 to "W" nail)  
20" I.Cedar, N.18°32'W., 32.5.Face healed. (N.20°W., 32.3)


TOWNSHIP 25 RANGE 02 POINT IDENTIFIER # 700540

PRIMARY CORNER DESCRIPTION E. 1/4 cor. for Sec. 12 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Fd. & used on BLM resurvey by A. Bert Skeesick & Daniel E. Weller, Cadastral Surveyors under Group #1888, surveyed Sept. 1998/Sept. 1999 - (DCSO rec. Vol. 53 Page(s) 20686-7)

Douglas Co. Surveyors Office - Crew: Stephen Flause & Jeff Lorsung- 5/17/2022 - C.S. File 67/54-7

-----  
Found - 2½" GL0 brass cap on 1" iron post, proj 6"  
Burnt 17"x30' D.Fir snag S.11°30'W., 17.5 ft. healed face.  
Sawn burnt 30"x1½' D.Fir stump N.53°W., 15.9 ft to added 3½" PK nail top center. Face healed.  
Burnt, sawn 32"x1' I.Cedar stump N.18°32'W., 32.5 ft healed face.  
2" IP with steel cap, Hosford mon. Loose from ground reset south 8.2 ft. proj 4'  
New - Burnt-dead 13" D.Fir S.66°E., 21.0 ft. 3½" PK nail right side center, no blaze or scribe.  
Burnt-sawn 20"x1½' Fir stump S.53°W., 4.9 ft. 3½" PK nail top center.  
Note - Area burnt 9/2020  
Compass decl. 14½°E.   
See sketch in file.  
Lat: 43°24'33.68"N Long: 122°52'26.47"W