

TOWNSHIP 25 RANGE 02 POINT IDENTIFIER # 700573

PRIMARY CORNER DESCRIPTION W. 1/4 Cor. Sec. 7, T25-1 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

V. W. Hosford, Surveyor - May 1949/Oct. 1950 - C.S. File 40/279 and M 12-61

I Set a 1" I.P. with steel cap from which
A Fir 18" dia., bears N.85½°E., 32.1 ft. mkd. T25S R1W ¼
S7 P.S. 253 BT.
A Fir 14" dia., bears S.46½°E., 11.6 ft. mkd. T25S R1W ¼
S7 P.S. 253 BT.

Fd. OK, DCS0, V. Tracy - May 1967 C.S. File 52/30-83

Survey by Steven Ness, L.S. #811 - For: Weyerhaeuser Co. -
Oct. 1995 - M 123-3 A & B

Found - 1 3/4" unmarked steel cap on 1¼" Iron post.
35" D.Fir stump, N.85°07'E., 33.2 ft., face healed.
Face has been sawn with a large wedge taken out.
27" D.Fir S.48°20'E., 12.0 ft., face healed.

Douglas Co. Surveyors Office - Crew: Stephen Flause & Jeff
Lorsung- 5/30/2024 - C.S. File 67/58-7

Found - 1¾" steel cap punch mark near center proj. 4"
Burned-rotted 26"X6 ft. D.Fir stump N.85°07'E., 33.2
ft. healed face.
Burned at base 34" D.Fir S.48°20'E., 12.0 ft. healed
face, add 3½" mag nail right side center.
New - Burned at base 22" D.Fir N.2°W., 27.5 ft. 3½" mag
nail right side center.
Burned at base 33" D.Fir N.14°E. 34.5 ft. 3½" mag
nail right side center.
Note - Area burnt 9/2020
Compass decl. 14½°E.
Mon in mixed old growth and reprod near top of east
bank of shallow SE running draw, creek @ S.45°W.,
20'±.

Oregon Coordinate Reference System
Cottage Grove - Canyonville Zone
N 212501.091 E 286083.281