

TOWNSHIP 25 RANGE 02 POINT IDENTIFIER # 700663

PRIMARY CORNER DESCRIPTION W. 1/4 Cor. for Sec. 6 only, T25-1

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

V. W. Hosford, Surveyor - May 1949/Oct. 1950 - C.S. File 40/279 and M 12-61

-----  
I set a 1" I.P. with steel cap, from which  
A Pine 32" dia., bears N.81°E., 27.9 ft. mkd. T25S R1W ¼  
S6 P.S. 253 BT.  
A Hemlock 24" dia., bears S.15°E., 49.2 ft. mkd. T25S R1W  
¼ S6 P.S. 253 BT.

May 1967, Searched for, not found - DCSO, V.Tracy C.S. File-52/30-84A

BLM resurvey by James E. Jelley, Cadastral Surveyor, under Group #1061 - Surveyed April/June 1981 - (DCSO records Vol. 45 Page(s) 17352-53)

-----  
The ¼ sec. cor. of sec. 6 only, established at proportionate dist. and recorded by Hosford, in 1950, is accepted as the cor. and is monumented with an iron pipe, 1¼" dia., firmly set, projecting 4" above ground, from which the remains of bearing trees mkd. by Hosford:

A sawed Fir stump 32" dia., bears N.81°E., 46 lks. dist. with scribe marks T25S R1W ¼ S6 RS 253 BT visible on opened blaze.

A sawed Sugar Pine stump 30" dia., bears S.16°E., 76½ lks. dist. with scribe marks T25S R1W ¼ S6 RS 253 BT visible on open blaze.

At the corner point

Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:

| T 25 S  
| 1/4 S 6  
| R 1 W  
1981

from which a new bearing tree:

A Fir 3" dia., bears S.41 3/4°E., 30½ lks. dist. mkd. X BT.

Deposit the iron pipe alongside the iron post.