

TOWNSHIP 25 RANGE 03E POINT IDENTIFIER # 100200

PRIMARY CORNER DESCRIPTION Cor Secs 30, 31; 25, & 36 T25-2E

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO Survey by John G. Collins, US Cadastral Engineer & Otto L. Draper, U.S. Transitman, under Special Instructions dated March 12, 1921, surveyed July 1928/Aug. 1930 - (DCSO records Vol. 22 Page(s) 9262-3)

-----  
Set an iron post, 3 ft. long, 2" dia., 26" in the ground, for cor. of secs. 25, 30, 31, & 36, with brass cap mkd

T25S

R2E	R3E
<u>S25</u>	<u>S30</u>
S36	S31

1928

from which

- A fir, 9" dia., bears N.37°E., 38 lks., mkd: T25S R3E S30  
BT.
- A fir, 40" dia., bears S.10°E., 9 lks., mkd: T25S R3E S31  
BT.
- A fir, 13" dia., bears S.75°W., 8 lks., mkd: T25S R2E S36  
BT.
- A fir, 18" dia., bears N.29°W., 42 lks., mkd: T25S R2E S25  
BT.