

TOWNSHIP 25 RANGE 03E POINT IDENTIFIER # 100300

PRIMARY CORNER DESCRIPTION Cor Secs 19, 30; 24, & 25 T25-2E

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO Survey by John G. Collins, US Cadastral Engineer & Otto L. Draper, U.S. Transitman, under Special Instructions dated March 12, 1921, surveyed July 1928/Aug. 1930 - (DCSO records Vol. 22 Page(s) 9264)

-----  
Set an iron post, 3 ft. long, 2" dia., 27" in the ground, for cor. of secs. 19, 24, 25, & 30, with brass cap mkd

T25S  
R2E|R3E  
S24|S19  
S25|S30  
1928

from which

- A fir, 6" dia., bears N.47°E., 25 lks., mkd: T25S R3E S19 BT.
- A fir, 4" dia., bears S.21°E., 15 lks., marked BT only.
- A fir, 6" dia., bears S.55°W., 27 lks., mkd: T25S R2E S25 BT.
- A fir, 5" dia., bears N.88°W., 12 lks., mkd: T25S R2E S24 BT.