

TOWNSHIP 25 RANGE 03E POINT IDENTIFIER # 100400

PRIMARY CORNER DESCRIPTION Cor. Secs. 18, 19; 13, & 24 T25-2E

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO Survey by John G. Collins, US Cadastral Engineer & Otto L. Draper, U.S. Transitman, under Special Instructions dated March 12, 1921, surveyed July 1928/Aug. 1930 - (DCSO records Vol. 22 Page(s) 9265)

Set an iron post, 3 ft. long, 2" dia., 16" in the ground, to bed rock and in mound of stone, 3½ ft. base, for cor. of secs. 13, 18, 19, & 24, with brass cap mkd

T25S
R2E|R3E
S13|S18
S24|S19
1928

from which

- A hemlock, 14" dia., bears N.60°E., 22 lks., mkd: T25S R3E S18 BT.
- A fir, 10" dia., bears S.51°E., 28 lks., mkd: T25S R3E S19 BT.
- A fir, 12" dia., bears S.64°W., 38 lks., mkd: T25S R2E S24 BT.
- A hemlock, 6" dia., bears N.54°W., 34 lks., mkd: T25S R2E S13 BT.