

TOWNSHIP 25 RANGE 03E POINT IDENTIFIER # 143700

PRIMARY CORNER DESCRIPTION South ¼ Sec. 31 T24-3E

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by John G. Collins, Cadastral Engineer, under Special Instr. dated March 12, 1921, Group No. 73; surveyed May/July 1926 - (DCSO records Vol. 22 Page(s) 9354-5)

-----  
Set an iron post, 3 ft. long, 1" dia., 6" in the ground, to bed rock, surrounded by a mound of stone, 3 ft. base, 2 ft. high, for ¼ sec. cor. of sec. 31 only, with brass cap marked  
¼ S31  
1926

from which

- A fir, 18" dia., bears N.64°E., 50 lks., mkd: ¼ S31 BT.
- A fir, 12" dia., bears N.37°W., 60 lks., mkd: ¼ S31 BT.

GLO survey by Otto L. Draper, US Transitman, under Special Instr. dated March 12, 1921, Group No. 74; surveyed June/Aug. 1931 - (DCSO records Vol. 22 Page(s) 9379)

-----  
The ¼ sec. cor. of sec. 31 only, which is an iron post, 1" dia., firmly set in mound of stone, 3½ ft. base, 2 ft. high, mkd. and witnessed as described in the official record.  
Thence, N.89°33'W., on true line bet. secs. 6 & 31  
At 1.83 chains North ¼ cor. sec. 6 only)