

TOWNSHIP 25 RANGE 03E POINT IDENTIFIER # 200300

PRIMARY CORNER DESCRIPTION Cor. Secs. 19, 20, 29, & 30

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Otto L. Draper, US Transitman, under Special Instr. dated March 12, 1921, Group No. 74; surveyed June/Aug. 1931 - (DCSO records Vol. 22 Page(s) 9442-3)

-----  
Set an iron post, 3 ft. long, 2" dia., 26" in the ground, for cor. of secs. 19, 20, 29, & 30, with brass cap mkd:

T25S	R3E
S19	S20
S30	S29
1931	

from which

- A fir, 501" dia., bears N.28°E., 118 lks., mkd: T25S R3E S20 BT.
- A cedar, 7" dia., bears S.71°E., 21 lks., mkd: T25S R3E S29 BT.
- A cedar, 10" dia., bears S.39°W., 96 lks., mkd: T25S R3E S30 BT.
- A fir, 18" dia., bears N.24°W., 41 lks., mkd: T25S R3E S19 BT.