

TOWNSHIP 25 RANGE 03E POINT IDENTIFIER # 203700

PRIMARY CORNER DESCRIPTION Cor. Secs. 31 & 32 only; T24-3E

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by John G. Collins, Cadastral Engineer, under Special Instr. dated March 12, 1921, Group No. 73; surveyed May/July 1926 - (DCSO records Vol. 22 Page(s) 9354)

-----  
Set an iron post, 3 ft. long, 2" dia., 28" in the ground, for cor. of secs. 31 & 32, with brass cap mkd:

T24S | R3E  
S31 | S32  
-----  
1926

from which

A fir, 12" dia., bears N.32°E., 33 lks., mkd: T24S R3E S32  
BT.

A fir, 16" dia., bears N.51°W., 55 lks., mkd: T24S R3E S31  
BT.

GLO survey by Otto L. Draper, US Transitman, under Special Instr. dated March 12, 1921, Group No. 74; surveyed June/Aug. 1931 - (DCSO records Vol. 22 Page(s) 9378-9)

-----  
The cor. of secs. 31 & 32 only, which is an iron post, 2" dia., 10" above ground, firmly set, mkd. and witnessed as described in the official record.

S.89°58'W., on true line bet. secs. 5 & 31

At 1.55 chains point for closing cor. of secs. 5 & 6.