

TOWNSHIP 25 RANGE 03E POINT IDENTIFIER # 240600

PRIMARY CORNER DESCRIPTION (WC) 1/4 Cor. Secs. 5 & 8

Alias 242600 Description PLSS for WC
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Otto L. Draper, US Transitman, under Special Instr. dated March 12, 1921, Group No. 74; surveyed June/Aug. 1931 - (DCSO records Vol. 22 Page(s) 9454)

S.89°45'W., on true line bet. secs. 5 & 8
At 39.95 chains
True point for ¼ sec. cor., falls on steep sloping bare rock, impracticable to set cor.
At 41.74 chains
Set an iron post, 3 ft. long, 1" dia., 20" in the ground, to ground, to bedrock, and in a mound of stone to top, for witness ¼ sec. cor., with brass cap marked

W C
¼ $\frac{S 5}{S 8}$
1931

from which
A fir, 22" dia., bears S.64°W., 223 lks., mkd: WC ¼ S8 BT.
A fir, 6" dia., bears N.22°W., 18 lks., mkd: WC ¼ S5 BT.
A Geological Survey bench mark, which is a brass cap, set in solid rock, on the point of Bulldog Rock, bears N.12°W., 169 lks. mkd "above sea 5836 ft"