

TOWNSHIP 25 RANGE 03E POINT IDENTIFIER # 243700

PRIMARY CORNER DESCRIPTION South 1/4 Cor. Sec. 32 only; T24-3E

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by John G. Collins, Cadastral Engineer, under Special Instr. dated March 12, 1921, Group No. 73; surveyed May/July 1926 - (DCSO records Vol. 22 Page(s) 9353-4)

Set an iron post, 3 ft. long, 1" dia., 28" in the ground, for ¼ sec. cor. of sec. 32, only, with brass cap marked

¼ S32
1926

from which

A hemlock, 10" dia., bears N.56°E., 45 lks., mkd: ¼ S32
BT.

A hemlock, 12" dia., bears N.61°W., 53 lks., mkd: ¼ S32
BT.

GLO survey by Otto L. Draper, US Transitman, under Special Instr. dated March 12, 1921, Group No. 74; surveyed June/Aug. 1931 - (DCSO records Vol. 22 Page(s) 9378)

The ¼ sec. cor. of sec. 32 only, which is an iron post, 1" dia., firmly set in mound of stone, 4 ft. base, 2 ft. high, mkd. and witnessed as described in the official record.

Thence N.89°49'W., on true line bet. secs. 5 & 32

At 1.59 chains The N ¼ cor. Sec. 5.