

TOWNSHIP 25 RANGE 03E POINT IDENTIFIER # 300300

PRIMARY CORNER DESCRIPTION Cor. Secs. 20, 21, 28, & 29

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Otto L. Draper, US Transitman, under Special Instr. dated March 12, 1921, Group No. 74; surveyed June/Aug. 1931 - (DCSO records Vol. 22 Page(s) 9427)

-----  
Set an iron post, 3 ft. long, 2" dia., 27" in the ground, for cor. of secs. 20, 21, 28, & 29, with brass cap mkd:

T25S	R3E
<u>S20</u>	<u>S21</u>
S29	S28
1931	

from which

- A fir, 12" dia., bears N.23°E., 32 lks., mkd: T25S R3E S21 BT.
- A fir, 14" dia., bears S.48°E., 78 lks., mkd: T25S R3E S28 BT.
- A hemlock, 16" dia., bears S.30°W., 94 lks., mkd: T25S R3E S29 BT.
- A fir, 56" dia., bears N.28°W., 76 lks., mkd: T25S R3E S20 BT.