

TOWNSHIP 25 RANGE 03E POINT IDENTIFIER # 300500

PRIMARY CORNER DESCRIPTION Cor. Secs. 8, 9, 16, & 17

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Otto L. Draper, US Transitman, under Special Instr. dated March 12, 1921, Group No. 74; surveyed June/Aug. 1931 - (DCSO records Vol. 22 Page(s) 9432)

-----  
Set an iron post, 3 ft. long, 2" dia., 27" in the ground, for cor. of secs. 8, 9, 16, & 17, with brass cap mkd:

T25S		R3E
S 8		S 9
S17		S16
1931		

from which

- A fir, 18" dia., bears N.14°E., 93 lks., mkd: T25S R3E S9 BT.
- A fir, 34" dia., bears S.69°E., 103 lks., mkd: T25S R3E S16 BT.
- A fir, 22" dia., bears S.79°W., 117 lks., mkd: T25S R3E S17 BT.
- A fir, 24" dia., bears N.37°W., 44 lks., mkd: T25S R3E S8 BT.