

TOWNSHIP 25 RANGE 03E POINT IDENTIFIER # 303700

PRIMARY CORNER DESCRIPTION Cor. Secs. 32 & 33 only T24-3E

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by John G. Collins, Cadastral Engineer, under Special Instr. dated March 12, 1921, Group No. 73; surveyed May/July 1926 - (DCSO records Vol. 22 Page(s) 9353)

Set an iron post, 3 ft. long, 2" dia., 28" in the ground, for cor. of secs. 32 & 33, with brass cap mkd:

T24S | R3E
S32 | S33
1926

from which

A hemlock, 8" dia., bears N.28°E., 21 lks., mkd: T24S R3E
S33 BT.

A fir, 15" dia., bears N.62½°W., 68 lks., mkd: T24S R3E
S32 BT.

GLO survey by Otto L. Draper, US Transitman, under Special Instr. dated March 12, 1921, Group No. 74; surveyed June/Aug. 1931 - (DCSO records Vol. 22 Page(s) 9377-8)

The cor. of secs. 32 & 33 only, which is an iron post, 2" dia., 8" above ground, firmly set, mkd. and witnessed as described in the official record.

N.89°54'W., on true line bet. secs. 4 & 32.

At 1.94 chains - Point for closing cor. of secs. 4 & 5.