

TOWNSHIP 25 RANGE 03E POINT IDENTIFIER # 343700

PRIMARY CORNER DESCRIPTION South ¼ Sec. 33, T24-3E

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by John G. Collins, Cadastral Engineer, under Special Instr. dated March 12, 1921, Group No. 73; surveyed May/July 1926 - (DCSO records Vol. 22 Page(s) 9352)

Set an iron post, 3 ft. long, 1" dia., 28" in the ground, for ¼ sec. cor. of sec. 33 only, with brass cap marked

¼ S33
1926

from which

A fir, 6" dia., bears N.1°E., 44 lks., mkd: ¼ S33 BT.

A fir, 30" dia., bears N.64°W., 43 lks., mkd: ¼ S33 BT.

GLO survey by Otto L. Draper, US Transitman, under Special Instr. dated March 12, 1921, Group No. 74; surveyed June/Aug. 1931 - (DCSO records Vol. 22 Page(s) 9377)

The ¼ sec. cor. of sec. 33 only, which is an iron post, 1" dia., 8" above ground, firmly set, mkd. and witnessed as described in the official record. Thence N.89°44;W., on true line bet. secs. 4 & 33 At 1.92 chains the N ¼ Sec. 4 only (PLSS 340700).