

TOWNSHIP 25 RANGE 03E POINT IDENTIFIER # 403700

PRIMARY CORNER DESCRIPTION Cor. Secs. 33 & 34; T24-3E

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by John G. Collins, Cadastral Engineer, under Special Instr. dated March 12, 1921, Group No. 73; surveyed May/July 1926 - (DCSO records Vol. 22 Page(s) 9352)

-----  
Set an iron post, 3 ft. long, 2" dia., 28" in the ground, for cor. of secs. 33 & 34 only, with brass cap mkd:

T24S | R3E  
S33 | S34  
-----  
1926

from which

A cedar, 40" dia., bears N.14°E., 229 lks., mkd: T24S R3E  
S34 BT.

A fir, 16" dia., bears N.73¾°W., 237 lks., mkd: T24S R3E  
S33 BT.

GLO survey by Otto L. Draper, US Transitman, under Special Instr. dated March 12, 1921, Group No. 74; surveyed June/Aug. 1931 - (DCSO records Vol. 22 Page(s) 9376)

-----  
The cor. of secs. 33 & 34 only, which is an iron post, 2" dia., 10" above ground, firmly set, mkd. and witnessed as described in the official record.

N.89°51'W., on true line bet. secs. 3 & 33.

At 1.76 chs Point for closing cor of secs 3 & 4 (PLSS 400700)