

TOWNSHIP 25 RANGE 03E POINT IDENTIFIER # 443700

PRIMARY CORNER DESCRIPTION South ¼ Sec. 34; T24-3E

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by John G. Collins, Cadastral Engineer, under Special Instr. dated March 12, 1921, Group No. 73; surveyed May/July 1926 - (DCSO records Vol. 22 Page(s) 9351)

Set an iron post, 3 ft. long, 1" dia., 28" in the ground, for ¼ sec. cor. of sec. 34 only, with brass cap marked

¼ S34
1926

from which

A fir, 36" dia., bears N.2½°E., 258 lks., mkd: ¼ S34 BT.

A fir, 30" dia., bears N.25°W., 223 lks., mkd: ¼ S34 BT.

GLO survey by Otto L. Draper, US Transitman, under Special Instr. dated March 12, 1921, Group No. 74; surveyed June/Aug. 1931 - (DCSO records Vol. 22 Page(s) 9375)

The ¼ sec. cor. of sec. 34 only, which is an iron post, 1" dia., 8" above ground, firmly set, mkd. and witnessed as described in the official record. Thence

N.89°57'W., on true line bet. secs. 3 & 34

At 1.70 chs (the N ¼ Sec. 3 only - PLSS 440700)