

TOWNSHIP 25 RANGE 03E POINT IDENTIFIER # 500200

PRIMARY CORNER DESCRIPTION Cor. Secs. 26, 27, 34, & 35

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Otto L. Draper, US Transitman, under Special Instr. dated March 12, 1921, Group No. 74; surveyed June/Aug. 1931 - (DCSO records Vol. 22 Page(s) 9397-8)

-----  
Set an iron post, 3 ft. long, 2" dia., 27" in the ground, for cor. of secs. 26, 27, 34, & 35, with brass cap mkd:

T25SR3E  
S27|S26  
S34|S35  
1931

from which

- A fir, 34" dia., bears N.62°E., 265 lks., mkd: T25S R3E S26 BT.
- A fir, 28" dia., bears S.25°E., 184 lks., mkd: T25S R3E S35 BT.
- A fir, 20" dia., bears S.52°W., 152 lks., mkd: T25S R3E S34 BT.
- A fir, 32" dia., bears N.52°W., 292 lks., mkd: T25S R3E S27 BT.