

TOWNSHIP 25 RANGE 03E POINT IDENTIFIER # 500240

PRIMARY CORNER DESCRIPTION (WC) 1/4 Cor. Secs. 26 & 27

Alias 500242 Description WC PLSS  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Otto L. Draper, US Transitman, under Special Instr. dated March 12, 1921, Group No. 74; surveyed June/Aug. 1931 - (DCSO records Vol. 22 Page(s) 9399-9400)

-----  
N.0°02'W., bet. secs. 26 & 27  
At 40.00 chains  
Point for the ¼ sec. cor., falls on precipitous slope impracticable to set cor.  
At 42.30 chains  
Set an iron post, 3 ft. long, 1" dia., 10" in the ground to bedrock, and in a mound of stone, to top, for witness ¼ sec. cor. secs. 26 & 27, with brass cap marked

¼  
S27|S26  
W|C  
1931

from which  
A hemlock, 16" dia., bears S.45°E., 81 lks., mkd: WC ¼ S26 BT.  
A fir, 34" dia., bears N.53°W., 93 lks., mkd: WC ¼ S27 BT.