

TOWNSHIP 25 RANGE 03E POINT IDENTIFIER # 500600

PRIMARY CORNER DESCRIPTION Cor. Secs. 2, 3, 10, & 11

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Otto L. Draper, US Transitman, under Special Instr. dated March 12, 1921, Group No. 74; surveyed June/Aug. 1931 - (DCSO records Vol. 22 Page(s) 9407)

-----  
Set an iron post, 3 ft. long, 2" dia., 27" in the ground, for cor. of secs. 2, 3, 10, & 11, with brass cap mkd:

T25S | R3E  
S 3 | S 2  
S10 | S11  
1931

from which

- A fir, 8" dia., bears N.26°E., 28 lks., mkd: T25S R3E S2  
BT.
- A fir, 10" dia., bears S.24°E., 25 lks., mkd: T25S R3E S11  
BT.
- A fir, 10" dia., bears S.39°W., 32 lks., mkd: T25S R3E S10  
BT.
- A fir, 10" dia., bears N.58°W., 11 lks., mkd: T25S R3E S3  
BT.