

TOWNSHIP 25 RANGE 03E POINT IDENTIFIER # 500700

PRIMARY CORNER DESCRIPTION CC Secs. 2 & 3

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Otto L. Draper, US Transitman, under Special Instr. dated March 12, 1921, Group No. 74; surveyed June/Aug. 1931 - (DCSO records Vol. 22 Page(s) 9409-10)

-----  
Set an iron post, 3 ft. long, 2" dia., 26" in the ground, for closing cor. of secs. 2 & 3, with brass cap mkd:

T24SR3E  
S34  
-----  
S 3 | S 2  
C | C  
T25SR3E  
1931

from which

A fir, 38" dia., bears S.17°E., 33 lks., mkd: T25S R3E S2  
CC BT.

A fir, 32" dia., bears S.41°W., 53 lks., mkd: T25S R3E S3  
CC BT.

From this point the cor. of secs. 34 & 35, T24-3E (PLSS 503700) bears N.89°56'E., 204 lks.