

TOWNSHIP 25 RANGE 03E POINT IDENTIFIER # 503700

PRIMARY CORNER DESCRIPTION Cor. Secs. 34 & 35 only; T24-3E

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by John G. Collins, Cadastral Engineer, under Special Instr. dated March 12, 1921, Group No. 73; surveyed May/July 1926 - (DCSO records Vol. 22 Page(s) 9350)

Set an iron post, 3 ft. long, 2" dia., 6" in the ground to bedrock, surrounded by mound of stone, 3 ft. base, 2 ft. high, for cor. of secs. 34 & 35, with brass cap mkd:

T24S | R3E
S34 | S35
1926

from which

A fir, 24" dia., bears N.21°E., 77 lks., mkd: T24S R3E S35
BT.

A fir, 18" dia., bears N.47°W., 43 lks., mkd: T24S R3E S34
BT.

GLO survey by Otto L. Draper, US Transitman, under Special Instr. dated March 12, 1921, Group No. 74; surveyed June/Aug. 1931 - (DCSO records Vol. 22 Page(s) 9375)

The cor. of secs. 34 & 35 only, which is an iron post, 2" dia., 8" above ground, firmly set, mkd. and witnessed as described in the official record.

S.89°56'W., on true line bet. secs. 2 & 34

At 2.04 chns pt for closing cor. of secs. 2 & 3 (PLSS 500700)