

TOWNSHIP 25 RANGE 03E POINT IDENTIFIER # 540700

PRIMARY CORNER DESCRIPTION N1/4 cor. Sec. 2 only

Alias 537700 Description WC N $\frac{1}{4}$ Sec. 2
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Otto L. Draper, US Transitman, under Special Instr. dated March 12, 1921, Group No. 74; surveyed June/Aug. 1931 - (DCSO records Vol. 22 Page(s) 9374)

From the 1/4 cor. of sec. 35 only, (PLSS 543700)

S.89°38'W., on true line bet. secs. 2 & 35

At 1.78 chains

Mid point bet. closing cors. as determined falls on face of bluff, impracticable to set cor.

At 2.30 chains

Set an iron post, 3 ft. long, 1" dia., 26" in the ground, for witness $\frac{1}{4}$ sec. cor. of sec. 2 only, with brass cap marked

W C

 $\frac{1}{4}$ S 2
1931

from which

A cedar, 24" dia., bears S.5°E., 29 lks., mkd: WC $\frac{1}{4}$ S2 BT.

A cedar, 16" dia., bears S.66°W., 50 lks. mkd: WC $\frac{1}{4}$ S2 BT.