

TOWNSHIP 25 RANGE 03E POINT IDENTIFIER # 543700

PRIMARY CORNER DESCRIPTION South ¼ Cor. Sec. 35 only; T24-3E

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by John G. Collins, Cadastral Engineer, under Special Instr. dated March 12, 1921, Group No. 73; surveyed May/July 1926 - (DCSO records Vol. 22 Page(s) 9349)

Set an iron post, 3 ft. long, 1" dia., 28" in the ground, for ¼ sec. cor. of 35 only, with brass cap marked

¼ S35
1926

from which

A fir, 12" dia., bears N.35½°E., 83 lks., mkd: ¼ S35 BT.

A fir, 10" dia., bears N.80°W., 76 lks., mkd: ¼ S35 BT.

GLO survey by Otto L. Draper, US Transitman, under Special Instr. dated March 12, 1921, Group No. 74; surveyed June/Aug. 1931 - (DCSO records Vol. 22 Page(s) 9374)

The ¼ sec. cor. of sec. 35 only, which is an iron post, 1" dia., 8" above ground, firmly set, mkd. and witnessed as described in the official record.

Thence S.89°38'W., on true line bet secs. 2 & 35

At 1.78 chains pt for ¼ cor. T25-3E (Falls on face of bluff)

At 2.30 chains pt for WC ¼ Cor. (PLSS 540700)