

TOWNSHIP 25 RANGE 03E POINT IDENTIFIER # 600300

PRIMARY CORNER DESCRIPTION Cor. Secs. 23, 24, 25, & 26

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Otto L. Draper, US Transitman, under Special Instr. dated March 12, 1921, Group No. 74; surveyed June/Aug. 1931 - (DCSO records Vol. 22 Page(s) 9384-5)

-----

Set an iron post, 3 ft. long, 2" dia., 24" in the ground, for cor. of secs. 23, 24, 25, & 26, with brass cap mkd:

T25S		R3E
S23		S24
S26		S25
1931		

from which

- A fir, 24" dia., bears N.69°E., 15 lks., mkd: T25S R3E S24  
BT.
- A fir, 14" dia., bears S.28°E., 70 lks., mkd: T25S R3E S25  
BT.
- A fir, 26" dia., bears S.14°W., 72 lks., mkd: T25S R3E S26  
BT.
- A fir, 18" dia., bears N.43°W., 20 lks., mkd: T25S R3E S23  
BT.