

TOWNSHIP 25 RANGE 03E POINT IDENTIFIER # 600600

PRIMARY CORNER DESCRIPTION (WC) Secs. 1, 2, 11, & 12

Alias 601600 Description WC PLSS  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Otto L. Draper, US Transitman, under Special Instr. dated March 12, 1921, Group No. 74; surveyed June/Aug. 1931 - (DCSO records Vol. 22 Page(s) 9393-4)

-----

Point for cor. of secs. 1, 2, 11, & 12, falls on face of bluff, impracticable to set cor. Thence N.89°54'E., 80 lks Set an iron post, 3 ft. long, 2" dia., 10" in the ground to bedrock and in a mound of stone to top for witness cor. of secs. 1, 2, 11, & 12, with brass cap mkd:

	W	C	
T25S		R3E	
S 2		S 1	
S11		S12	
1931			

from which

- A fir, 16" dia., bears N.58°E., 43 lks., mkd: W C T25S R3E S1 BT.
- A fir, 24" dia., bears S.48°E., 78 lks., mkd: W C T25S R3E S12 BT.
- A fir, 20" dia., bears S.32°W., 35 lks., mkd: W C T25S R3E S12 BT.
- A fir, 22" dia., bears N.65°W., 42 lks., mkd: W C T25S R3E S1 BT.