

TOWNSHIP 25 RANGE 03E POINT IDENTIFIER # 603700

PRIMARY CORNER DESCRIPTION South Cor. Secs. 35 & 36 only: T24-3E

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by John G. Collins, Cadastral Engineer, under Special Instr. dated March 12, 1921, Group No. 73; surveyed May/July 1926 - (DCSO records Vol. 22 Page(s) 9348)

Set an iron post, 3 ft. long, 2" dia., 18" in the ground, to bed rock, surrounded by a mound of stone, 3 ft. base, 1 ft. high, for cor. of secs. 35 & 36, with brass cap mkd:

T24S | R3E
S35 | S36
1926

from which

A fir, 8" dia., bears N.58½°E., 95 lks., mkd: T24S R3E S36
BT.

A fir, 8" dia., bears N.18°W., 85 lks., mkd: T24S R3E S35
BT.

GLO survey by Otto L. Draper, US Transitman, under Special Instr. dated March 12, 1921, Group No. 74; surveyed June/Aug. 1931 - (DCSO records Vol. 22 Page(s) 9373 & 9396)

The cor. of secs. 35 & 36 only, which is an iron post, 2" dia., firmly set in a mound of stone 4 ft. base, 2 ft. high mkd. and witnessed as described in official record.

S.89°28'W., on true line bet. secs. 1 & 35

At 1.82 chains

(Point for closing cor. of secs. 1 & 2 PLSS 600700)