

TOWNSHIP 25 RANGE 03E POINT IDENTIFIER # 643700

PRIMARY CORNER DESCRIPTION South ¼ Sec. 36 T24-3E

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by John G. Collins, Cadastral Engineer, under Special Instr. dated March 12, 1921, Group No. 73; surveyed May/July 1926 - (DCSO records Vol. 22 Page(s) 9347)

Set an iron post, 3 ft. long, 1" dia., 28" in the ground, for ¼ sec. cor. of sec. 36 only, with brass cap marked
¼ S36
1926

from which

- A fir, 36" dia., bears N.56°E., 113 lks., mkd: ¼ S36 BT.
- A fir, 8" dia., bears N.80°W., 134 lks., mkd: ¼ S36 BT.

GLO survey by Otto L. Draper, US Transitman, under Special Instr. dated March 12, 1921, Group No. 74; surveyed June/Aug. 1931 - (DCSO records Vol. 22 Page(s) 9372-3)

The ¼ sec. cor. of sec. 36 only, which is an iron post, 1" dia., 9" above ground, firmly set, mkd. and witnessed as described in the official record.
Thence N.89°58'W., on true line bet. secs. 1 & 36.
At 0.57 chains
(Set 1/4 cor. sec. 1 T25-3E only - see PLSS 640700)