

TOWNSHIP 25 RANGE 03E POINT IDENTIFIER # 700400

PRIMARY CORNER DESCRIPTION Cor. Secs. 13, 24; 18 & 29

Alias \_\_\_\_\_ Description (Sec. 18 T25-4E = PB 40)  
Alias \_\_\_\_\_ Description (Sec. 19 T25-4E = PB 41)  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Otto L. Draper, US Transitman, under Special Instr. dated March 12, 1921, Group No. 74; surveyed June/Aug. 1931 - (DCSO records Vol. 22 Page(s) 9367)

-----  
Set an iron post, 3 ft. long, 2" dia., 26" in the ground, for cor. of secs. 13, 18, 19, & 24, with brass cap mkd:

T25S  
R3E | S4E  
S13 | S18  
S24 | S19  
1931

from which

- A fir, 28" dia., bears N.49°E., 55 lks., mkd: T25S R4E S18  
BT.
- A fir, 26" dia., bears S.37°E., 67 lks., mkd: T25S R4E S19  
BT.
- A fir, 22" dia., bears S.72°W., 76 lks., mkd: T25S R3E S24  
BT.
- A fir, 16" dia., bears N.33°W., 55 lks., mkd: T25S R3E S13  
BT.