

TOWNSHIP 25 RANGE 03E POINT IDENTIFIER # 700500

PRIMARY CORNER DESCRIPTION Cor. Secs. 12, 13; 7 & 18 T25-4E

Alias \_\_\_\_\_ Description (Sec. 7 T25-4E = PB 39)  
Alias \_\_\_\_\_ Description (Sec. 18 T25-4E = PB 40)  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Otto L. Draper, US Transitman, under Special Instr. dated March 12, 1921, Group No. 74; surveyed June/Aug. 1931 - (DCSO records Vol. 22 Page(s) 9368)

-----  
Set an iron post, 3 ft. long, 2" dia., 22" in the ground to bedrock, and in a mound of stone to top, for cor. of secs. 7, 12, 13, & 18, with brass cap mkd:

T25S  
R3E|R4E  
S12|S 7  
S13|S18  
1931

from which

- A fir, 42" dia., bears N.58°E., 56 lks., mkd: T25S R4E S7  
BT.
- A fir, 34" dia., bears S.26°E., 42 lks., mkd: T25S R4E S18  
BT.
- A fir, 38" dia., bears S.74°W., 70 lks., mkd: T25S R3E S13  
BT.
- A fir, 50" dia., bears N.67°W., 70 lks., mkd: T25S R3E S12  
BT.