

TOWNSHIP 25 RANGE 03 POINT IDENTIFIER # 100140

PRIMARY CORNER DESCRIPTION 1/4 Cor. Sec. 31; & 36 of T25-4

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - W.H. Byars, Contract #152 dated June, 1871  
(DCSO records, Volume 9 Page Page 3667)

-----  
Set 1/4 sec. post, from which  
A Fir 18" dia. bears S.80°E., 7 lks. dist.  
A Fir 12" dia. bears S.50°W., 7 lks. dist.

C.E. Roberts - For: J.S. Hunt - May 28, 1903 - FB 7 Page 8-9

-----  
Reset Post.  
Madrone 10" N.72°W., 10 lks.  
Cedar 48" S.59°E., 31 lks.

Bureau of Land Management Dependent Resurvey - Norman D. Price  
Special Instructions dated April 5, 1940 - Survey, 1943  
(DCSO records, Volume 27, Page 11520-21)

-----  
Point for orig. 1/4 cor. determined at the record measurements  
from both old bearing trees.  
At point for corner, set an iron post, 3 ft. long, 1" dia. 28"  
in the ground, for 1/4 sec. cor., with brass cap mkd:

1/4  
|  
S36|S31  
1943                      from which

A Fir 30" dia. bears S.70°E., 7 lks. dist. mkd. on bark  
1/4 S B T. I re-blaze and re-mark this old bearing  
tree 1/4 S 31 B T.  
A Fir stump 14" dia. bears S.45°W., 7 lks. dist. with  
only axe marks (old BT)  
A Fir 22" dia. bears N.42 1/2°W., 45 lks. dist. mkd. 1/4  
S 36 B T. (New BT)

Found OK, 1958 Dependent Resurvey - Zirpel, Corbin and  
Roseberry (DCSO records, Volume 29 Page 12262)

Douglas Co. Surveyors Office - Stephen J. Flause - John Pike  
- 9/26/2007 - C.S. File 67/24-27

-----  
Found - 2 1/2" dia., brass cap marked as per rec. on 1" O.D.  
iron pipe, projects 22" above ground. Base of  
iron pipe appears undisturbed.  
30" now 25" dia. burnt fir snag, approx 50 ft. tall,  
tagged, no marks visible, bears S.70°E., 6.6 ft  
to center of root crown, 1943 rec. dist. would  
fit well as a face meas. (1943 rec. S.70°E.,  
4.6 OBT)                      continued next page

TOWNSHIP 25 RANGE 03 POINT IDENTIFIER # 100140

PRIMARY CORNER DESCRIPTION 1/4 Cor. Sec. 31; & 36 of T25-4

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

<p>22" Fir now blow down is tagged - no position; root hole indeterminate (rec. N.42½°W., 29.7 ft.) 1943 BT</p> <p>No trace of any other BTs noted.</p> <p>New - 14" dia., D.Fir double blazed &amp; scribed "¼ S31 CS BT" bears S.57°E., 30.0 ft.</p> <p>"X" chiseled into face of sandstone outcrop "X" is approx. 4" tall bears N.20°W., 7.3 ft.</p> <p>17" dia., D.Fir, pistol butt, double blazed &amp; scribed "¼ S36 CS BT" bears S.52½°W., 47.5 ft.</p> <p>Note - Corner lies in bottom of steep draw with BC/IP in bed of seasonal drainage. Drains N.70°E., Put mound of stone around BC/IP Compass decl. 16¼°E.</p>	
--	--